



Hex head Exe stopping plug

Technical Specifications

Nickel Plated Type - Metric	Thread Size Metric (mm)	Brass Type - Metric	Thread Size Metric (mm)	Stainless Steel Type - Metric	Thread Size Metric (mm)
EXN/M16/HSP	16	EX/M16/HSP	16	EXS/M16/HSP	16
EXN/M20/HSP	20	EX/M20/HSP	20	EXS/M20/HSP	20
EXN/M25/HSP	25	EX/M25/HSP	25	EXS/M25/HSP	25
EXN/M32/HSP	32	EX/M32/HSP	32	EXS/M32/HSP	32
EXN/M40/HSP	40	EX/M40/HSP	40	EXS/M40/HSP	40
EXN/M50/HSP	50	EX/M50/HSP	50	EXS/M50/HSP	50
EXN/M63/HSP	63	EX/M63/HSP	63	EXS/M63/HSP	63

N.B. PG stopping plugs available upon request



Dome head Exe stopping plug

Nickel Plated Type - Metric	Thread Size Metric (mm)	Brass Type - Metric	Thread Size Metric (mm)	Stainless Steel Type - Metric	Thread Size Metric (mm)
EXN/M16/DSP	16	EX/M16/DSP	16	EXS/M16/DSP	16
EXN/M20/DSP	20	EX/M20/DSP	20	EXS/M20/DSP	20
EXN/M25/DSP	25	EX/M25/DSP	25	EXS/M25/DSP	25
EXN/M32/DSP	32	EX/M32/DSP	32	EXS/M32/DSP	32
EXN/M40/DSP	40	EX/M40/DSP	40	EXS/M40/DSP	40
EXN/M50/DSP	50	EX/M50/DSP	50	EXS/M50/DSP	50
EXN/M63/DSP	63	EX/M63/DSP	63	EXS/M63/DSP	63

N.B. PG stopping plugs available upon request



Nylon stopping plug



Nylon Type - Metric	Thread Size Metric (mm)
EX-M16	16
EX-M20	20
EX-M25	25
EX-M32	32
EX-M40	40
EX-M50	50
EX-M63	63

Certification & Standards

Nylon Stopping Plug

EC TYPE Examination Certificate:

IMQ 13 ATEX 016X, IECEx IMQ 13.0005X

Exe IIC Gb

Ex tb III Db

IP test: IP66-IP68

Accessories

Technical Specifications



Coupler - female to female thread couplers for use in both Exd and Exe applications



Nickel Plated Type - Metric	Thread Size Metric (mm)
EXN/M16/C	16
EXN/M20/C	20
EXN/M25/C	25
EXN/M32/C	32
EXN/M40/C	40
EXN/M50/C	50
EXN/M63/C	63
EXN/M75/C	75

Brass Type - Metric	Thread Size Metric (mm)
EX/M16/C	16
EX/M20/C	20
EX/M25/C	25
EX/M32/C	32
EX/M40/C	40
EX/M50/C	50
EX/M63/C	63
EX/M75/C	75

Stainless Steel Type - Metric	Thread Size Metric (mm)
EXS/M16/C	16
EXS/M20/C	20
EXS/M25/C	25
EXS/M32/C	32
EXS/M40/C	40
EXS/M50/C	50
EXS/M63/C	63
EXS/M75/C	75

Nickel Plated Type - NPT	Thread Size NPT (inch)
EXN/038/C	3/8
EXN/050/C	1/2
EXN/075/C	3/4
EXN/100/C	1
EXN/125/C	1 1/4
EXN/150/C	1 1/2
EXN/200/C	2
EXN/250/C	2 1/2

Brass Type - NPT	Thread Size NPT (inch)
EX/038/C	3/8
EX/050/C	1/2
EX/075/C	3/4
EX/100/C	1
EX/125/C	1 1/4
EX/150/C	1 1/2
EX/200/C	2
EX/250/C	2 1/2

Stainless Steel Type - NPT	Thread Size NPT (inch)
EXS/038/C	3/8
EXS/050/C	1/2
EXS/075/C	3/4
EXS/100/C	1
EXS/125/C	1 1/4
EXS/150/C	1 1/2
EXS/200/C	2
EXS/250/C	2 1/2

Certification Standard: Baseefa 08 ATEX 0359U
IECEx BAS08.0121U
TÜV11.0158U

Ex de IIC Gb
Ex tb IIIC Db

Temperature: -60°C to +200°C



Hex locknut

Nickel Plated Type - Metric	Thread Size Metric (mm)
WHMM03	16
WHMM04	20
WHMM05	25
WHMM06	32
WHMM07	40
WHMM08	50
WHMM09	63

Brass Type - Metric	Thread Size Metric (mm)
WHMB03	16
WHMB04	20
WHMB05	25
WHMB06	32
WHMB07	40
WHMB08	50
–	63

Stainless Steel Type - Metric	Thread Size Metric (mm)
–	16
MXWH04	20
MXWH05	25
MXWH06	32
MXWH07	40
MXWH08	50
–	63

Nickel Plated Type - NPT	Thread Size NPT (inch)
–	3/8
WHAM04	1/2
WHAM05	3/4
WHAM06	1
WHAM07	1 1/4
WHAM08	1 1/2
WHAM09	2

Brass Type - NPT	Thread Size NPT (inch)
–	3/8
WHAB04	1/2
WHAB05	3/4
WHAB06	1
WHAB07	1 1/4
WHAB08	1 1/2
–	2

Stainless Steel Type - NPT	Thread Size NPT (inch)
–	3/8
MXAH04	1/2
MXAH05	3/4
MXAH06	1
MXAH07	1 1/4
MXAH08	1 1/2
–	2