



Star Teck Extreme Director™ (STED) series Adjustable range-taking cable gland



Approvals / Characteristics



Features

- First truly adjustable, range-taking fitting
- Exclusive swash-plate design allows adjustments from 90 to 180 degrees
- Full circular bore for trouble-free cable insertion
- Alignment guides facilitate installation of fittings at same angle
- Requires no disassembly prior to installation; can also be easily disconnected
- For use with teck cable, jacketed metal-clad cable (ACWU) or metal clad cable (MC)

Certification and standards

UL Listed and CSA Certified for hazardous locations as outlined in the CEC:

UL E38947

CSA 023086, AEX

Class I, Class II groups E, F & G


Class III and enclosures Type 4, 4x and 6P

Exe II IP68

Dimensions

Technical specifications

Assembly:



Installation steps

Caution: De-energise system



Install fitting into enclosure



Insert cable and tighten (as usual)



Rotate fitting to desired angle

Type	Hub Size	Gland Torque (lb - in)	Range Over Jacket (in)		Range Over Armour (in)		Throat Dia.	Throat Dia.	Overall (in)
			Min.	Max.	Min.	Max.	Min (in) w/ Armour Stop	Min (in) w/o Armour Stop	
STED050	1/2"	450	0.600	0.885	0.520	0.795	0.505	0.617	5.375
STED075	3/4"	600	0.860	1.205	0.780	1.125	0.645	0.819	5.875