Safeline Series



Eaton's Safeline Series is an Industrial Interchange pneumatic coupling with push button safety feature designed for use with compressed air. Two-step disconnect procedure shuts off air supply and releases downstream air pressure before plug can be removed from socket/female, which prevents hose whip.

Product Features

- Safe and easy to connect and disconnect
- Light weight, compact ergonomic design
- Accepts 1/4" ISO 6150 Series B and A-A-59439 plugs/males
- Accepts all US Idustrial plugs/ males
- Standard body material: Aluminum
- Standard seal material: Buna-N


Physical Characteristics


Series	Max. Operating	Pressure	Min. Burst Pre	ssure	Rated Flow		
	(bar)	(psi)	(bar)	(psi)	(lpm)	scfm	
GD10500	16	232	64	928	566	20	

Applications & Markets

- General Pneumatics
- Air Tools
- Industrial Plants
- Maintenance and Repair

Flow Data





Hex




Figure 1

Figure 2 Figure 3

Male End Connections

Part	Coupling	Body Size	Port				Dimen	Dimensions				
Number	Туре		Size	Thread	Type	Fig.	Α	В	Hex	Α	В	Hex
							(in)	(in)	(in)	(mm)	(mm)	(mm)
GD1053641	Socket/Female	1/4	1/4	1/4	NPT	1	3.20	1.02	0.67	81.3	25.9	17.0
GD1053683	Socket/Female	1/4	3/8	3/8	NPT	1	3.18	1.02	0.75	80.8	25.9	19.1

Female End Connections

Part	Coupling	Body Size	Port	Dimensions									
Number	Туре		Size	Thread	Type	Fig.	Α	В	Hex	Α	В	Hex	
							(in)	(in)	(in)	(mm)	(mm)	(mm)	
GD1052641	Socket/Female	1/4	1/4	1/4	NPT	2	2.98	1.02	0.67	75.7	25.9	17.0	
GD1052683	Socket/Female	1/4	3/8	3/8	NPT	2	3.18	1.02	0.87	80.8	25.9	22.1	

Hose Stem End Connections

Part	Coupling	Body	Hose		Dimen	sions				
Number	Туре	Size	I.D.	Fig.	Α	В	Hex	Α	В	Hex
					(in)	(in)	(in)	(mm)	(mm)	(mm)
GD1055601	Socket/Female	1/4	3/8	3	3.58	1.02	0.67	90.9	25.9	17.0