## **5X Series Fittings**

AY



O Adapters & Valves

D Quick Couplings



Type "M" Female

Swivel

B-14


Material:

5X Series

Crimp Fittings

> Nipple - Very high strength stainless steel SD / SUBSEA - High strength corrosion-resistant stainless steel Shell and Nut - Stainless steel

C9



Medium Pressure

Tube Nipple

B-15

Y2

ſ

Part Number			ninal .D.		Thread Size	A Overall Length		B Cutoff Allowance		J Hex		Maximum Working Pressure*	
#	0									$\bigcirc$		$\bigcirc$	
	DN	Size	inch	mm		inch	mm	inch	mm	inch	mm	psi	bar
6AY5X-11-8C	12	-08	1/2	12.7	1" - 12	4.25	108	1.72	44	1.250	32	-	—
6AY5X-16-12C	20	-12	3/4	19	1- <sup>5</sup> /16" - 12	4.26	108	1.52	39	1.500	38	Ι	_
6AY5X-16-12C-INC725	20	-12	3/4	19	1-5/16" - 12	4	102	1.25	32	1.500	38	Ι	—
6AY5X-11-8C- SUBSEA	12	-08	1/2	12.7	1" - 12	4.22	107	1.98	50	1.250	32		_
1AY5X-11-08C-M- SUBSEA	12	-08	1/2	12.7	1"-12	4.42	112	1.87	47	1.250	32	_	-

Metric Female

Swivel

B-14

\* Fitting is rated to the full working pressure of the hose

## 6C95X- Metric Female Swivel

Material: Nipple - Very high strength stainless steel

Shell - Stainless steel Nut - Carbon steel, zinc-plated



Part Number	Nominal I.D.				Thread Size	A Overall Length		B Cutoff Allowance		H Hex		Maximum Working Pressure*	
#	0							$\bigcirc$					
	DN	N Size inch mm			inch	mm	inch	mm	inch	mm	psi	bar	
6C95X-25-12C	20	-12	3/4	19.0	M 36 x 2	4.37	111	1.60	41	1.810	46	-	—

\* Fitting is rated to the full working pressure of the hose



This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## **5X Series Fittings**

## 1Y25X/6Y25X- Medium Pressure Tube Nipple

Material: Nipple - Very high strength stainless steel SUBSEA - High strength corrosion resistant stainless steel Shell - Stainless steel



Part Number	Nominal I.D.				Thread Size	A Overall Length		B Cutoff Allowance		R Diameter		Maximum Working Pressure	
#	0				<u></u>					Ø		$\bigcirc$	
	DN	Size	inch	mm		inch	mm	inch	mm	inch	mm	psi	bar
6AY5X-16-12C-INC725	20	-12	3/4	19.0	1"-14 LH	7.17	182	5.07	129	1.500	38	20,000	1,380
6Y25X-16-12C-SL	20	-12	3/4	19.0	1"-14 LH	4.83	123	2.73	69	1.690	43	20,000	1,380
1Y25X-9-08C-M- SUBSEA	12	-08	1/2	12.7	9/16"-18 LH	6.69	174	4.31	109	1.339	34	20,000	1,380
1Y25X-12-08C-M- SUBSEA	12	-08	1/2	12.7	3/4"-16 LH	7.25	184	4.70	119	1.339	34	20,000	1,380

**B** Fittings

A Hose

WARNING This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. D Quid