

5,5

 = 25 mm²


14



Other designs in series 14

The following other designs can be found from page:

► Brass / Steel P. 46

Technical Description

Safety coupling with a self-venting system according to ISO C. Self-venting takes place during disconnection – no risk of pressurised hoses being tossed around. When the sleeve is pulled back, the plug is released yet remains locked in. The coupling valve closes and the air is vented from the air line at the same time. Only then, by operating the sleeve again, can uncoupling take place safely. The system fulfils the requirements of ISO 4414 – increased safety standards in the work place. The plastic sleeve does not scratch working surfaces.

Safety Note

Reliable functioning can only be guaranteed in conjunction with original Parker Rectus plugs made of steel.

Working Temperature*

-20°C up to +60°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +60°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.



Working Pressure**

12 bar

** maximum static working pressure with design factor 4 to 1.

Material


Coupling: Brass nickel plated

Plug: Steel nickel plated

Seals: NBR

Flow diagrams




Air





Couplings – with valve




Series 14KE

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	22		58	9		31				14KEAK13MPN
	R 3/8	22		58	9		31				14KEAK17MPN
	R 1/2	24		63	12		31				14KEAK21MPN
 <p>Female Thread</p>	G 1/4	22		57	9		31				14KEIW13MPN
	G 3/8	22		57	9		31				14KEIW17MPN
	G 1/2	24		60	12		31				14KEIW21MPN
 <p>Hose Barb</p>	6 mm	22		71	25		31				14KETF06MPN
	8 mm	22		71	25		31				14KETF08MPN
	9 mm	22		71	25		31				14KETF09MPN
	10 mm	22		71	25		31				14KETF10MPN
	13 mm	22		71	25		31				14KETF13MPN



Plugs – without valve

Series 22SF

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/8	12		35	9						22SFAK10SXN
	R 1/4	14		41	12						22SFAK13SXN
	R 3/8	17		41	12						22SFAK17SXN
	R 1/2	22		46	17						22SFAK21SXN
 <p>Female Thread</p>	G 1/4	17		35	9						22SFIW13SXN
	G 3/8	19		35	10						22SFIW17SXN
	G 1/2	24		38	12						22SFIW21SXN
 <p>Hose Barb</p>	6 mm			49	25		12				22SFTF06SXN
	8 mm			49	25		12				22SFTF08SXN
	9 mm			49	25		12				22SFTF09SXN
	10 mm			49	25		12				22SFTF10SXN
	13 mm			49	25		12				22SFTF13SXN