

SUPERIOR PROTECTION

Synthetic Lubricant and Coolant

For rotary screw air compressors

- AEON 9000SP is a PAO (polyalphaolefin)/MFSE (multifunctional synthetic ester) synthetic blend tested and proven to provide optimum operating and service-life results.
- A highly robust blend formulated to withstand high temperatures, varnish/sludge formation, and environmental contamination.
- A unique additive package designed specifically to maximize compressor efficiency and provide optimum lubricity.
- A proven track record of superior service-life in the most rugged operating environments.

Don't Take a Chance . . .
Use Only Original Gardner Denver AEON
Lubricants!





AEON 9000SP ADVANTAGES

- Superior thin-film protection for compressor internal components.
- Extended service life to 8,000 hours*, reduces downtime and disposal costs.
- Superior oxidation stability vs. other competitive brands.
- Free Oil Analysis Program.
- Completely demulsible separates quickly, reduces condensate disposal costs.
- Minimizes oil carryover, reduces "make-up" costs.
- Compatible with all common air system seals.
- High flash point improves your safety margin.
- Non-hazardous, disposable with mineral-based compressor lubricants.

All compressed air systems require dry, clean air and environmentally sound disposal of by products. That is why Gardner Denver's support does not stop at the compressor.

Rust, oil vapors, wear particles, air pollution, industrial gases and humidity all can foul pressurized air flows. Proper removal of these contaminates is essential in preventing costly damage to tools, and equipment.

To ensure total system reliability, Gardner Denver provides a broad range of dryers, coalescing filters, oil/water separators, drains, cleaning fluids, and aftercoolers. ONE-STOP shopping from Gardner Denver assures that all components of the system are designed to work together and are backed by customer support today and for years to come.

SELECTED PHYSICAL PROPERTIES

PROPERTY	TEST METHOD/RESULTS
Viscosity, cSt	ASTM D445
at 40C	49.01
at 100C	7.83
at 100F	54.04
at 210F	8.02
ISO Viscosity Grade	46
Pour Point F/C	ASTM D97 - < -65/-54
Flash Point F/C	ASTM D92 - 500/260
Demulsibility	ASTM D1401 - 40/40/0 (<1min.)
Color	Lilac

^{*}Recommended service intervals depend on (1) clean ambient conditions, (2) filter and separator changes as required in compressor service and operating manual, and (3) "normal" compressor temperature conditions. NOTE: Laboratory analysis of compressor fluids should be used to determine lubricant service life.

CONVENIENT PACKAGE SIZES

PACKAGE SIZE	PART #
5 Gallon	28H109
55 Gallon	28H110

A complete family of compressors and ancillary products is offered by Gardner Denver.

HMIS HAZARD ID

Health: O Flammability: 1 Reactivity: O Handling: B

Not a controlled product under Canadian WHMIS criteria



For additional information contact your local representative or Gardner Denver Compressor Division, 1800 Gardner Expressway, Quincy, Illinois 62301 Customer Service Department Telephone: (800) 682-9868 FAX: (217) 228-8243 Sales and Service in all major cities. For parts information, contact Gardner Denver,

For parts information, contact Gardner Denver, Master Distribution Center, Memphis, TN Telephone: (800) 245-4946 FAX: (901) 542-6159



©2005 Gardner Denver, Inc.
http://www.gardnerdenver.com respon
Bulletin 9-1-220 2nd Ed 3/05

respond@gardnerdenver.com

