

Compression Fittings

Brass Compression Fittings

Stainless Steel Compression Fittings

PL Nickel-Plated Brass Spigot Fittings





Compression Fittings

Brass Compression Fittings (P. 5-5)



Fluids: compressed air, non-corrosive industrial fluids
Materials: forged or machined brass
Pressure: 550 bar
Temperature: -40°C to +250°C
Ø metric: 4 mm to 28 mm

Stainless Steel Compression Fittings (P. 5-31)



Fluids: compressed air, coolants, industrial and corrosive fluids
Materials: 316L stainless steel
Pressure: 400 bar
Temperature: -40°C to +250°C
Ø metric: 6 mm to 16 mm

PL Nickel-Plated Brass Spigot Fittings (P. 5-41)



Fluids: compressed air, compatible industrial fluids
Materials: forged or machined nickel-plated brass
Pressure: 40 bar
Temperature: -40°C to +100°C
Ø metric: 4 mm to 14 mm

Compression Fitting Part Numbers

Item Type	0105142799	Suffix
01XX: brass 18XX: stainless steel		39: bonded seal 40: treated steel 60: nut 70: polymer nut 99: chemical nickel
	Ø	Thread
	04 = 4 mm 06 = 6 mm ... 20 = 20 mm 28 = 28 mm	10 = 1/8 13 = 1/4 ... 21 = 1/2 27 = 3/4

PL Fitting Part Numbers

Item Type	F3BPL8/10-1/4	Thread
FBPL F3BPL HBPL WBPL ...	Ø	BSPT & NPT: 1/8 1/4 3/8 ... Metric: M10 M12
	2.7/4 4/6 6/8 7.5/10 8/10 10/12 11/14	

Brass Compression Fitting Range

Brass Fittings

Stud Fittings

0105
BSPT
Page 5-9



0105
NPT
Page 5-9



0101
BSPP/Metric
Page 5-10



0101..39
BSPP
Page 5-10



0101
Metric
Page 5-11



0114
BSPP
Page 5-11



0109
BSPT
Page 5-12



0109
NPT
Page 5-12



0199
BSPP
Page 5-12



0108
BSPT
Page 5-13



0103
BSPT
Page 5-13



0118
BSPP
Page 5-14



0118..39
BSPP
Page 5-14



0119
BSPP
Page 5-15



0119..39
BSPP
Page 5-15



Tube-to-Tube Fittings

0106
Page 5-15



0113
Page 5-16



0116
Page 5-16



0102
Page 5-16



0104
Page 5-17



0142
Page 5-17



0107
Page 5-17



Complementary Fittings

0166
Page 5-20



0124
Page 5-21



0124..40
Page 5-21



0111
Page 5-21



0110
Page 5-22



0110..40
Page 5-22



0110..60
Page 5-22



0110..70
Page 5-22



Self-Fastening Hose Barb Connectors

0132
Page 5-25



0133..39
Page 5-25



0134
Page 5-25



Accessories

0122
Page 5-26



0165
Page 5-26



0126
Page 5-27



0125
Page 5-27



0220
Page 5-27



0220..39
Page 5-27



0120
Page 5-28



0112
Page 5-28



0128..39
Page 5-29



0151..39
Page 5-29



0168..39
Page 5-29



0127
Page 5-30



Brass Compression Fittings

These **"universal"** fittings provide users with **numerous connection** options for a wide variety of tube materials without the need for tube threading or soldering. This range **guarantees** excellent long-term sealing and performance.

Product Advantages

Simple to Install and Use

- Suitable for pneumatic and medium pressure hydraulic applications
- Compatible with many industrial fluids
- Large product range: 22 configurations
- Excellent sealing due to the tightening of the olive onto the tube
- Metallic sealing guarantees maximum service life
- High strength brass for increased mechanical reliability

Wide Variety of Tubing

- Connection of different types of tubing and hose: metal, polymer, steel, rubber, etc.
- Multiple tube diameters can be connected using the Parker Legris reducer assembly system
- No insert required for rigid and semi-rigid polyamide tubing below 14 mm



Applications


- Pneumatics
- Cooling
- Automotive Process
- Lubrication
- Fluid Transmission
- Packaging
- Industrial Machinery

Technical Characteristics

Compatible Fluids	Water, machining oil, fuel, hydraulic oil, compressed air, chemical fluids, disinfectants
Working Pressure	Vacuum to 550 bar
Working Temperature	-40°C to +250°C
Tightening Torque	See "Technical Characteristics" on opposite page

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Maximum Bore Diameters

The table below shows the recommended compatibility of tube size, BSPP male thread and maximum bore.

Tube O.D.	BSPP Thread	Max. Bore
4-5-6	G1/8	4
6-8-10	G1/4	7
10-12-14	G3/8	11
14-15-16-18	G1/2	14
18-20-22	G3/4	18
22-25-28	G1	24

Tube Length for Assembly

Minimum length of tube (L) between 2 fittings.



ØD	L (mm)	ØD	L (mm)	ØD	L (mm)
4	26.5	12	39	20	51
5	26	14	41	22	54
6	26	15	41	25	62
8	32	16	46.5	28	62
10	39	18	49.5		

Regulations

CNOMO: E07.21.115N
(for robotic equipment in the automotive industry)
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)
DI: 2002/95/EC (RoHS)
DI: 94/9/EC (ATEX)

Technical Characteristics

Installing Compression Fittings

Cutting the Tube



Cut the polymer or metal tube square.

Preparing the Connection



For metal tubing, de-burr the tube prior to connection. Tube bending should be done before connection.



Slide the nut onto the tube; lubricate the threads on the body and nut along with the olive to facilitate tightening (for metal tubing as well). Fit the olive onto the end of the tube.

Connecting the Tube



Push the tube up against the shoulder of the body of the fitting and hand tighten.

Final Assembly




Tighten the nut using a spanner or torque wrench to enable the olive to bite on the tube, the connection being completed when the recommended tightening torque is reached (see tables below).




It is recommended to use an insert in order to prevent tube creeping (diameter > 14mm)

Recommended Nut Tightening Torque

Tightening torque in daN.m =
maximum tightening torque of a 0110 nut and 0124 olive with copper, brass or steel tube.



Nut 0110 and 0110..40



Nut 0110..60

Ø D (mm)	Ø F 0110	Ø F 0110..60	Max. daN.m Copper or Brass	Ø F 0110..40	Max. daN.m Steel
4	10	11	0.7	10	1.5
5	12	13	0.7	12	1.5
6	13	13	1.5	13	2.5
8	14	16	1.5	14	2.5
10	19	20	1.8	19	3
12	22	22	3	22	4.5
14	24	24	3.5	24	5.5
15	24	24	4	24	6
16	27	27	5	27	7
18	30	30	6	30	9
20	32	32	6	32	10
22	36	36	7	36	12
25	41	41	8	41	13
28	42		9		

Customised Fittings

Working directly with its customers and based on its knowledge and experience, Parker Legris can design customised brass compression fittings for specific requirements using the customer's specifications.

The range of compression fittings also offers nickel chemical surface treatment in order to improve the corrosion resistance and chemical compatibility of the fittings (the model number of the fitting is then given the suffix 99).

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.



Technical Characteristics

The use of Parker Legris brass compression fittings is dependant on the tube material. Tables of recommended working pressure for the different tubes are shown below.

Recommended Tube Type

Copper tube: copper which has been "cold rolled", cold drawn and in straight lengths.

Brass tube: in cold-rolled straight lengths (same working pressure as for copper tube).

"Coiled annealed" copper tube: reduces working pressure by 35%; must be avoided completely if vibration is present.

Steel tube: "thin wall" cold drawn, seamless, bright annealed and in straight lengths.
6 mm to 16 mm O.D.: max. wall thickness 1 mm
Above 16 mm O.D.: max. wall thickness 1.5 mm




Polyamide tube: semi-rigid
For rigid polyamide tube, multiply the figures in this table by 1.8.

Recommended Tube-Fitting Assembly Configurations

Assembled using Parker Legris brass olive and nut.

Assembled using Parker Legris steel olive and nut (nut type 0110..40).

Assembled using Parker Legris brass olive and nut.



When using a plastic nut type 0110..70, the maximum working pressure is 10 bar, for all diameters.

Working Pressure Coefficients for Semi-Rigid Polyamide Tubing

Temperature °C	-40°C / -15°C	-15°C / +30°C	+30°C / +50°C	+50°C / +70°C	+70°C / +100°C
Factor	1.8	1	0.68	0.55	0.31

Parker Legris brass compression fittings are not compatible with ammonia and its derivatives.

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.


Brass Compression Fittings

0105

Stud Fitting, Male BSPT Thread



Brass



ØD	C		F	F1	H _{max}	H1	kg
4	R1/8	0105 04 10	10	10	17	7	0.012
	R1/8	0105 05 10	11	12	17.5	7.5	0.016
5	R1/4	0105 05 13	14	12	17.5	7.5	0.022
	R1/8	0105 06 10	11	13	18	7.5	0.017
6	R1/4	0105 06 13	14	13	18	7.5	0.024
	R3/8	0105 06 17	17	13	18	8.5	0.031
	R1/8	0105 08 10	13	14	19.5	7	0.020
8	R1/4	0105 08 13	14	14	19.5	7	0.025
	R3/8	0105 08 17	17	14	20.5	8	0.032
	R1/8	0105 10 10	17	19	24	9	0.043
10	R1/4	0105 10 13	17	19	24	9	0.047
	R3/8	0105 10 17	17	19	24	9	0.048
	R1/2	0105 10 21	22	19	25	10	0.067
	R1/4	0105 12 13	19	22	24	9	0.059
12	R3/8	0105 12 17	19	22	24	9	0.060
	R1/2	0105 12 21	22	22	25	10	0.076
	R1/4	0105 14 13	22	24	25	8	0.068
14	R3/8	0105 14 17	22	24	25	8	0.068
	R1/2	0105 14 21	22	24	26	9	0.080
	R3/4	0105 14 27	27	24	27	10	0.107
15	R3/8	0105 15 17	22	24	25	8	0.065
	R1/2	0105 15 21	22	24	26	9	0.076
	R1/4	0105 16 13	24	27	27	9.5	0.092
16	R3/8	0105 16 17	24	27	27	9.5	0.092
	R1/2	0105 16 21	24	27	27	9.5	0.099
	R3/4	0105 16 27	27	27	28	10.5	0.123
18	R1/2	0105 18 21	27	30	30	10.5	0.127
	R3/4	0105 18 27	27	30	30	10.5	0.138
20	R1/2	0105 20 21	30	32	32	11	0.148
	R3/4	0105 20 27	30	32	32	11	0.157
	R1/2	0105 22 21	32	36	33	11	0.187
22	R3/4	0105 22 27	32	36	33	11	0.196
	R1	0105 22 34	36	36	33	11	0.227
25	R3/4	0105 25 27	36	41	36	11	0.261
	R1	0105 25 34	36	41	36	11	0.278
28	R3/4	0105 28 27	41	42	36	11	0.274
	R1	0105 28 34	41	42	36	11	0.283

Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

Brass Compression Fittings


Compression Fittings

0105

Stud Fitting, Male NPT Thread



Brass



ØD	C		F	F1	H _{max}	H1	kg
6	NPT1/8	0105 06 11	11	13	18	7.5	0.018
	NPT1/4	0105 06 14	14	13	18	7.5	0.027
8	NPT1/8	0105 08 11	13	14	21	7	0.021
	NPT1/4	0105 08 14	14	14	18.5	7	0.026
	NPT1/4	0105 10 14	17	19	24	9	0.048
10	NPT3/8	0105 10 18	17	19	24	9	0.048
	NPT1/2	0105 10 22	22	19	25	10	0.066


Brass Compression Fittings

0101

Stud Fitting with Captive Sealing Washer, Male BSPP and Metric Thread



Brass, technical polymer



ØD	C		E	F	F1	H _{max}	H1	kg
4	M5x0.8	0101 04 19	5	10	10	16.5	8	0.011
	G1/8	0101 04 10	6.5	13	10	16.5	8	0.016
5	G1/8	0101 05 10	6.5	13	12	17.5	8.5	0.018
	G1/8	0101 06 10	6.5	13	13	18	8.5	0.020
6	G1/4	0101 06 13	8	17	13	18	9.5	0.030
	G1/8	0101 08 10	6.5	13	14	19	8.5	0.021
8	G1/4	0101 08 13	8	17	14	19.5	9	0.032
	G3/8	0101 08 17	11	22	14	20	10.5	0.044
10	G1/4	0101 10 13	8	17	19	24	11	0.049
	G3/8	0101 10 17	11	22	19	24	11.5	0.061
12	G1/4	0101 12 13	8	19	22	24	11	0.062
	G3/8	0101 12 17	11	22	22	24	11.5	0.069
	G1/2	0101 12 21	12	27	22	24	12	0.089
14	G3/8	0101 14 17	11	22	24	25	10.5	0.074
	G1/2	0101 14 21	12	27	24	25	11	0.094
	G3/8	0101 15 17	11	22	24	25	10.5	0.071
15	G1/2	0101 15 21	12	27	24	25	11	0.093
	G3/8	0101 16 17	11	22	27	27	12	0.092
	G1/2	0101 16 21	12	27	27	27	12.5	0.109
18	G1/2	0101 18 21	12	27	30	29.5	12.5	0.128
	G3/4	0101 18 27	13	32	30	29.5	13	0.152
20	G3/4	0101 20 27	13	32	32	31	13	0.164
	G3/4	0101 22 27	13	32	36	32	13	0.195
22	G1	0101 22 34	15	41	36	31	13.5	0.259
	G3/4	0101 25 27	13	36	41	35.5	13	0.261
25	G1	0101 25 34	15	41	41	35.5	13	0.169
28	G1	0101 28 34	15	41	42	35.5	13.5	0.300


With pre-assembled captive sealing washer
Sealing washers 0602 are shown in Chapter 9.

0101..39

Stud Fitting, with Bi-Material Seal, Male BSPP



Brass, zinc-plated steel with NBR seal



ØD	C		E	F	F1	H _{max}	H1	kg
4	G1/8	0101 04 10 39	5.5	13	10	17.5	9	0.016
5	G1/8	0101 05 10 39	5.5	13	12	18.5	9.5	0.019
	G1/8	0101 06 10 39	5.5	13	13	19	9.5	0.020
6	G1/4	0101 06 13 39	7	17	13	19	10.5	0.030
	G1/8	0101 08 10 39	5.5	13	14	20	9.5	0.022
8	G1/4	0101 08 13 39	7	17	14	20.5	10	0.032
	G3/8	0101 08 17 39	9.5	22	14	21.5	12	0.045
10	G1/4	0101 10 13 39	7	17	19	25	12	0.048
	G3/8	0101 10 17 39	9.5	22	19	25.5	13	0.062
	G1/4	0101 12 13 39	7	19	22	25	12	0.063
12	G3/8	0101 12 17 39	9.5	22	22	25	13	0.071
	G1/2	0101 12 21 39	10.5	27	22	25	13.5	0.091
14	G3/8	0101 14 17 39	9.5	22	24	26.5	12	0.075
	G1/2	0101 14 21 39	10.5	27	24	26.5	12.5	0.095
	G3/8	0101 15 17 39	9.5	22	24	26.5	12	0.073
15	G1/2	0101 15 21 39	10.5	27	24	26.5	12.5	0.095
	G3/8	0101 16 17 39	9.5	22	27	28.5	13.5	0.092
16	G1/2	0101 16 21 39	10.5	27	27	28.5	14	0.111
	G1/2	0101 18 21 39	10.5	27	30	31	14	0.129
18	G3/4	0101 18 27 39	11.5	32	30	31	14.5	0.155
20	G3/4	0101 20 27 39	11.5	32	32	32.5	14.5	0.164
	G3/4	0101 22 27 39	11.5	32	36	32.5	14.5	0.197
22	G1	0101 22 34 39	13	41	36	33	15.5	0.259
25	G1	0101 25 34 39	13	41	41	37.5	15.5	0.309
28	G1	0101 28 34 39	13	41	42	37.5	15.5	0.301

Thread with bi-material seal
Bi-material sealing washers, part number 0139, can be found in Chapter 9


Brass Compression Fittings

0101

Stud Fitting, Male Metric Thread



Brass



ØD	C		E	F	F1	H _{max}	H1	kg
4	M7x1	0101 04 55	6.5	10	10	16.5	7.5	0.012
	M8x1	0101 04 56	6.5	11	10	16.5	7.5	0.013
5	M8x1	0101 05 56	6.5	11	12	17.5	8	0.016
	M10x1	0101 05 60	6.5	14	12	17.5	8.5	0.020
6	M10x1	0101 06 60	6.5	14	13	18	8.5	0.021
	M10x1.5	0101 06 62	6.5	14	13	18	8.5	0.021
8	M12x1	0101 08 65	8	17	14	19.5	9	0.029
	M12x1.25	0101 08 66	8	17	14	19.5	9	0.029
10	M13x1.25	0101 08 68	8	17	14	19.5	9	0.030
	M14x1.25	0101 10 70	8	17	19	24	11	0.047
10	M14x1.5	0101 10 71	8	17	19	24	11	0.047
	M16x1.25	0101 10 74	9	19	19	24	11	0.051
10	M16x1.5	0101 10 75	9	19	19	24	11	0.051
	M18x1.5	0101 10 78	9	22	19	24	11.5	0.060
12	M16x1.25	0101 12 74	9	19	22	24	11	0.061
	M16x1.5	0101 12 75	9	19	22	24	11	0.061
12	M18x1.5	0101 12 78	9	22	22	24	11.5	0.070
	M18x1.5	0101 14 78	9	22	24	25	10.5	0.077
14	M20x1.5	0101 14 80	10	24	24	25	11	0.084
	M18x1.5	0101 15 78	9	22	24	25	10.5	0.071
16	M20x1.5	0101 16 80	10	24	27	27	12.5	0.102
	M22x1.5	0101 16 82	10	27	27	27	12.5	0.111
18	M22x1.5	0101 18 82	10	27	30	29.5	12.5	0.129
	M24x1.5	0101 18 83	11	30	30	29.5	13	0.142


Brass Compression Fittings

0114

Stud Fitting, Female BSPP Thread



Brass



ØD	C		E	F	F1	H _{max}	H1	kg
4	G1/8	0114 04 10	9.5	14	10	26	16.5	0.020
	G1/4	0114 04 13	13.5	17	10	30	20.5	0.030
5	G1/8	0114 05 10	9.5	14	12	28	17	0.023
	G1/4	0114 05 13	13.5	17	12	31	21	0.033
6	G1/8	0114 06 10	9.5	14	13	28	17	0.025
	G1/4	0114 06 13	13.5	17	13	32	21	0.034
8	G3/8	0114 06 17	14	22	13	32	21.5	0.051
	G1/8	0114 08 10	9.5	14	14	29	16.5	0.026
8	G1/4	0114 08 13	13.5	17	14	33	20.5	0.036
	G3/8	0114 08 17	14	22	14	34	21	0.052
10	G1/4	0114 10 13	13.5	17	19	37	21.5	0.052
	G3/8	0114 10 17	14	22	19	37	22	0.068
10	G1/2	0114 10 21	18.5	27	19	42	26.5	0.099
	G1/4	0114 12 13	13.5	19	22	36	20.5	0.069
12	G3/8	0114 12 17	14	22	22	37	22	0.078
	G1/2	0114 12 21	18.5	27	22	42	26.5	0.109
14	G1/4	0114 14 13	13.5	22	24	36	18.5	0.085
	G3/8	0114 14 17	14	22	24	38	21	0.048
15	G1/2	0114 14 21	18.5	27	24	43	25.5	0.113
	G3/8	0114 15 17	14	22	24	38	21	0.078
15	G1/2	0114 15 21	18.5	27	24	43	25.5	0.109
	G1/4	0114 16 13	13.5	24	27	36	18	0.107
16	G3/8	0114 16 17	14	24	27	38	20.5	0.106
	G1/2	0114 16 21	18.5	27	27	44	26	0.127
18	G3/8	0114 18 17	14	27	30	39	19.5	0.140
	G1/2	0114 18 21	18.5	27	30	45	26	0.144
18	G3/4	0114 18 27	19.5	32	30	46	27	0.165
	G3/8	0114 20 17	14	30	32	38	18	0.161
20	G1/2	0114 20 21	18.5	30	32	44.5	24	0.173
	G3/4	0114 20 27	19.5	32	32	47	26.5	0.170
22	G3/4	0114 22 27	19.5	32	36	48	26.5	0.204
25	G3/4	0114 25 27	19.5	36	41	50.5	26	0.297

Compression Fittings

Brass Compression Fittings

0109

Stud Elbow, Male BSPT Thread

Brass

ØD	C		F	H	J	L _{max}	L1	kg
4	R1/8	0109 04 10	10	17	8	19	9.5	0.016
	R1/4	0109 04 13	10	20	10	19	11	0.026
5	R1/8	0109 05 10	12	17.5	8	21	11	0.019
	R1/4	0109 05 13	12	21.5	10	22	12	0.028
6	R1/8	0109 06 10	13	18	8	22	11	0.021
	R1/4	0109 06 13	13	21.5	10	22	12	0.031
8	R1/8	0109 08 10	14	18.5	10	28	15	0.028
	R1/4	0109 08 13	14	22	10	28	15	0.033
10	R3/8	0109 08 17	14	24	12	28	15	0.044
	R1/4	0109 10 13	19	25	12	30	14.5	0.052
	R3/8	0109 10 17	19	25.5	12	30	14.5	0.060
	R1/2	0109 10 21	19	32	19	36	21	0.109
12	R1/4	0109 12 13	22	26	15	30	15	0.074
	R3/8	0109 12 17	22	27	15	30	15	0.077
14	R1/2	0109 12 21	22	32	19	36	21	0.116
	R3/8	0109 14 17	24	30	19	35	18	0.105
	R1/2	0109 14 21	24	32	19	35	18	0.112
15	R3/8	0109 15 17	24	30	19	35	18	0.099
	R1/2	0109 15 21	24	32	19	35	18	0.106
16	R3/8	0109 16 17	27	30	19	39	21	0.120
	R1/2	0109 16 21	27	33.5	19	39	21	0.130
	R3/4	0109 16 27	27	36.5	23	41	23	0.189
18	R1/2	0109 18 21	30	35.5	23	41	21.5	0.182
	R3/4	0109 18 27	30	36.5	23	41	21.5	0.199
20	R1/2	0109 20 21	32	36.5	23	42	21.5	0.181
	R3/4	0109 20 27	32	38	23	42	21.5	0.200
22	R3/4	0109 22 27	36	40	27	50	30	0.288
	R1	0109 22 34	36	44	27	50	30	0.342
25	R3/4	0109 25 27	41	43	27	54	30	0.325
	R1	0109 25 34	41	44	27	54	30	0.367
28	R3/4	0109 28 27	42	46	32	54	30	0.402
	R1	0109 28 34	42	48	32	54	30	0.384

Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

0109

Stud Elbow, Male NPT Thread

Brass

ØD	C		F	H	J	L _{max}	L1	kg
6	NPT1/8	0109 06 11	13	18	8	22	11	0.021
	NPT1/4	0109 06 14	13	21.5	10	22	12	0.030
8	NPT1/8	0109 08 11	14	18.5	10	28	15	0.028
	NPT1/4	0109 08 14	14	22	10	28	15	0.033
10	NPT1/4	0109 10 14	19	25	12	30	14.5	0.053

0199

Stud Orientable Elbow, Male BSPP Thread

Brass, NBR

ØD	C		F	F1	H	H1	H1 max	J	L max	L1	kg
4	G1/8	0199 04 10	14	10	23	16	17	8	19	9.5	0.023
	G1/4	0199 04 13	19	10	30.5	22	23.5	10	19	11	0.043
6	G1/8	0199 06 10	14	13	23	16	17	8	22	11	0.027
	G1/4	0199 06 13	19	13	30.5	22	23.5	10	22	12	0.047
8	G1/8	0199 08 10	14	14	24	17	18	10	28	15	0.033
	G1/4	0199 08 13	19	14	30.5	22	23.5	10	28	15	0.051
	G3/8	0199 08 17	22	14	33.5	24	25.5	12	28	15	0.065
10	G1/4	0199 10 13	19	19	31	22.5	24	12	30	14.5	0.068
	G3/8	0199 10 17	22	19	33.5	24	25.5	12	30	14.5	0.079
14	G1/2	0199 10 21	27	19	40	29.5	31	19	37	22	0.138
	G3/8	0199 14 17	22	24	35.5	26	27.5	19	35	18	0.119
18	G1/2	0199 14 21	27	24	40	29.5	31	19	35	18	0.141
	G1/2	0199 18 21	27	30	40	29	30.5	23	41	21.5	0.187
22	G3/4	0199 18 27	32	30	43.5	32	33.5	23	41	21.5	0.222
	G3/4	0199 22 27	32	36	45.5	34	36	32	51	31	0.382
28	G1	0199 22 34	41	36	54	40.5	43	32	51	31	0.408
	G1	0199 28 34	41	42	54	40.5	43	32	54	30	0.420

The body will orientate for positioning purposes


Brass Compression Fittings

0108

Stud Branch Tee, Male BSPT Thread



Brass



ØD	C		F	H	J	L1	L/2	kg
4	R1/8	0108 04 10	10	17	8	9.5	19	0.025
5	R1/8	0108 05 10	12	17.5	8	11	21	0.017
6	R1/8	0108 06 10	13	18	8	11	22	0.032
	R1/4	0108 06 13	13	21.5	10	16	27	0.047
8	R1/8	0108 08 10	14	18.5	10	15	28	0.045
	R1/4	0108 08 13	14	22	10	15	28	0.050
	R3/8	0108 08 17	14	24	12	15	28	0.061
	R1/4	0108 10 13	19	25	12	14.5	30	0.084
10	R3/8	0108 10 17	19	25.5	12	14.5	30	0.090
	R1/4	0108 12 13	22	26	15	15	30	0.116
12	R3/8	0108 12 17	22	27	15	15	30	0.117
	R3/8	0108 14 17	24	30	19	18	35	0.153
14	R1/2	0108 14 21	24	32	19	18	35	0.168
	R3/8	0108 15 17	24	30	19	18	35	0.145
15	R1/2	0108 15 21	24	32	19	18	35	0.155
	R3/8	0108 16 17	27	30	19	21	39	0.190
16	R1/2	0108 16 21	27	33.5	19	21	39	0.203
	R1/2	0108 18 21	30	35.5	23	21.5	41	0.265
18	R3/4	0108 18 27	30	36.5	23	21.5	41	0.292
	R3/4	0108 20 27	32	38	23	21.5	42	0.298
20	R3/4	0108 22 27	36	40	27	29	50	0.435
	R1	0108 22 34	36	44	27	29	50	0.466


Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.

0103

Stud Run Tee, Male BSPT Thread



Brass



ØD	C		F	H max	H1	H2	J	kg
4	R1/8	0103 04 10	10	19	17	9.5	8	0.025
5	R1/8	0103 05 10	12	21	17.5	11	8	0.030
6	R1/8	0103 06 10	13	22	18	11	8	0.033
	R1/4	0103 06 13	13	27	21.5	16	10	0.048
8	R1/8	0103 08 10	14	28	18.5	15	10	0.045
	R1/4	0103 08 13	14	28	22	15	10	0.050
	R3/8	0103 08 17	14	28	24	15	12	0.061
	R1/4	0103 10 13	19	30	25	14.5	12	0.084
10	R3/8	0103 10 17	19	30	25.5	14.5	12	0.092
	R1/4	0103 12 13	22	30	26	15	15	0.114
12	R3/8	0103 12 17	22	30	27	15	15	0.120
	R3/8	0103 14 17	24	35	30	18	19	0.161
14	R1/2	0103 14 21	24	35	32	18	19	0.169
	R3/8	0103 15 17	24	35	30	18	19	0.148
15	R1/2	0103 15 21	24	35	32	18	19	0.158
	R3/8	0103 16 17	27	39	30	21	19	0.192
16	R1/2	0103 16 21	27	39	33.5	21	19	0.199
	R1/2	0103 18 21	30	41	35.5	21.5	23	0.269
18	R3/4	0103 18 27	30	41	36.5	21.5	23	0.282
	R3/4	0103 20 27	32	42	38	21.5	23	0.298
20	R3/4	0103 20 27	32	42	38	21.5	23	0.298
22	R3/4	0103 22 27	36	50	40	29	27	0.435

Metric taper threads or Briggs (NPT threads) are available by special order, subject to minimum quantities.


Brass Compression Fittings

0118

Single Banjo, with Captive Sealing Washer, Male BSPP Thread



Brass, technical polymer



ØD	C		F	F1	H	H1	L _{max}	L1	N	kg
4	G1/8	0118 04 10	14	10	24	9.5	24	14.5	17.5	0.038
5	G1/8	0118 05 10	14	12	24	9.5	25	14.5	17.5	0.041
	G1/4	0118 05 13	17	12	25	10	26	16	21	0.058
6	G1/8	0118 06 10	14	13	24	9.5	25	14.5	17.5	0.041
	G1/4	0118 06 13	17	13	25	10	26	16	21	0.056
8	G1/8	0118 08 10	14	14	24	9.5	28	15.5	17.5	0.054
	G3/8	0118 08 13	17	14	25	10	28	15.5	21	0.057
10	G1/4	0118 10 13	17	19	31	13	34	19	23	0.120
	G3/8	0118 10 17	22	19	32	13	34	19	26.5	0.129
12	G1/4	0118 12 13	17	22	34	14.5	34	19	23	0.126
	G3/8	0118 12 17	22	22	35	14.5	34	19	26.5	0.133
14	G1/4	0118 14 13	17	24	37	16	37	20.5	28	0.154
	G3/8	0118 14 17	22	24	38	16	37	20.5	28	0.195
15	G1/2	0118 14 21	27	24	40	16	38	20.5	32.5	0.208
	G3/8	0118 15 17	22	24	38	16	37	20.5	28	0.190
16	G1/2	0118 15 21	27	24	40	16	38	20.5	32.5	0.198
	G3/8	0118 16 21	27	27	42	16	38	21	32.5	0.221
18	G1/2	0118 18 21	27	30	46	19.5	43	24.5	36	0.366
20	G3/4	0118 20 27	32	32	49	20	44	24.5	39	0.403
22	G3/4	0118 22 27	32	36	53	22	45	24.5	39	0.459


With pre-assembled captive sealing washer
Sealing washers 0602 can be found in Chapter 9.

0118..39

Single Banjo with Bi-Material Seal, Male BSPP Thread



Brass, zinc-plated steel with NBR seal



ØD	C		F	F1	H	H1	L _{max}	L1	N	kg
4	G1/8	0118 04 10 39	14	10	23	9.5	24	14.5	17.5	0.038
5	G1/8	0118 05 10 39	14	12	23	9.5	25	14.5	17.5	0.041
	G1/4	0118 05 13 39	17	12	24	10	26	16	21	0.064
6	G1/8	0118 06 10 39	14	13	23	9.5	25	14.5	17.5	0.042
	G1/4	0118 06 13 39	17	13	24	10	26	16	21	0.057
8	G1/8	0118 08 10 39	14	14	23	9.5	28	15.5	17.5	0.055
	G3/8	0118 08 13 39	17	14	24	10	28	15.5	21	0.058
10	G1/4	0118 10 13 39	17	19	30	13	34	19	23	0.118
	G3/8	0118 10 17 39	22	19	31.5	13.5	34	19	26.5	0.128
12	G1/4	0118 12 13 39	17	22	33	14.5	34	19	23	0.128
	G3/8	0118 12 17 39	22	22	34.5	15	34	19	26.5	0.140
14	G1/4	0118 14 13 39	17	24	36	16	37	20.5	28	0.189
	G3/8	0118 14 17 39	22	24	37.5	16.5	37	20.5	28	0.198
15	G1/2	0118 14 21 39	27	24	39	16.5	38	20.5	32.5	0.205
	G3/8	0118 15 17 39	22	24	37.5	16.5	37	20.5	28	0.389
16	G1/2	0118 15 21 39	27	24	40	16.5	38	20.5	32.5	0.202
	G3/8	0118 16 21 39	27	27	40	16.5	38	21	32.5	0.225
18	G1/2	0118 18 21 39	27	30	47	20	43	24.5	36	0.369
20	G3/4	0118 20 27 39	32	32	50	20.5	44	24.5	39	0.394
22	G3/4	0118 22 27 39	32	36	54	22.5	45	24.5	39	0.462

With bi-material sealing washer
Bi-material sealing washers, part number 0139, can be found in Chapter 9.


Brass Compression Fittings

0119

Double Banjo with Captive Sealing Washer, Male BSPP Thread



Brass, technical polymer



ØD	C		F	F1	H	H1	L1	L/2	N	kg
4	G1/8	0119 04 10	14	10	24	9.5	14.5	24	17.5	0.049
6	G1/8	0119 06 10	14	13	24	9.5	14.5	25	17.5	0.056
	G1/4	0119 06 13	17	13	25	10	16	26.5	21	0.038
8	G1/8	0119 08 10	14	14	24	9.5	15.5	28	17.5	0.069
	G1/4	0119 08 13	17	14	25	10	15.5	28	21	0.074
10	G3/8	0119 08 17	22	14	32	13	18	30.5	26.5	0.140
	G1/4	0119 10 13	17	19	31	13	19	34	23	0.156
12	G3/8	0119 10 17	22	19	32	13	19	34	26.5	0.165
	G1/4	0119 12 13	17	22	34	14.5	19	34	23	0.180
14	G3/8	0119 12 17	22	22	35	14.5	19	34	26.5	0.182
	G1/4	0119 14 13	17	24	37	16	20.5	37.5	28	0.246
14	G3/8	0119 14 17	22	24	38	16	20.5	37.5	28	0.247
	G1/2	0119 14 21	27	24	40	16	20.5	38	32.5	0.219

Thread with pre-assembled washer


Sealing washers 0602 can be found in Chapter 9.

0119..39

Double Banjo with Bi-Material Seal, Male BSPP Thread



Brass, zinc-plated steel with NBR seal



ØD	C		F	F1	H	H1	L1	L/2	N	kg
4	G1/8	0119 04 10 39	14	10	23	9.5	14.5	24	17.5	0.050
5	G1/8	0119 05 10 39	14	12	23	9.5	14.5	25	17.5	0.049
	G1/4	0119 05 13 39	17	12	24	10	126	26	21	0.072
6	G1/8	0119 06 10 39	14	13	23	9.5	14.5	25	17.5	0.056
	G1/4	0119 06 13 39	17	13	24	10	16	26	21	0.071
8	G1/8	0119 08 10 39	14	14	23	9.5	15.5	28	17.5	0.072
	G1/4	0119 08 13 39	17	14	24	10	15.5	28	21	0.080
10	G3/8	0119 08 17 39	22	14	31.5	13.5	18	30	26.5	0.118
	G1/4	0119 10 13 39	17	19	30	13	19	34	23	0.156
12	G3/8	0119 10 17 39	22	19	31.5	13.5	19	34	26.5	0.167
	G1/4	0119 12 13 39	17	22	33	14.5	19	34	23	0.180
14	G3/8	0119 12 17 39	22	22	34.5	15	19	34	26.5	0.183
	G1/4	0119 14 13 39	17	24	36	16	20.5	37	28	0.248
14	G3/8	0119 14 17 39	22	24	37.5	16.5	20.5	37	28	0.247
	G1/2	0119 14 21 39	27	24	39	16.5	20.5	38	32.5	0.262
15	G3/8	0119 15 17 39	22	24	37.5	16.5	20.5	37	28	0.246
	G1/2	0119 15 21 39	27	24	40	16.5	20.5	38	32.5	0.251
18	G1/2	0119 18 21 39	27	30	47	20	24.5	43	36	0.469
20	G3/4	0119 20 27 39	32	32	50	20.5	24.5	44	39	0.638
22	G3/4	0119 22 27 39	32	36	54	22.5	24.5	45	39	0.610

Thread with pre-assembled washer


Bi-material sealing washers, part number 0139, can be found in Chapter 9.

0106

Equal Tube-to-Tube Connector




Brass




ØD		F	F1	L _{max}	L1	kg
4	0106 04 00	10	10	28	10	0.016
5	0106 05 00	11	12	31	11	0.023
6	0106 06 00	11	13	32	11	0.026
8	0106 08 00	13	14	36	10	0.031
10	0106 10 00	17	19	42	13	0.070
12	0106 12 00	19	22	42	13	0.092
14	0106 14 00	22	24	45	11	0.104
15	0106 15 00	22	24	45	11	0.097
16	0106 16 00	24	27	48	13	0.141
18	0106 18 00	27	30	53	14	0.186
20	0106 20 00	30	32	56	14	0.211
22	0106 22 00	32	36	60	14	0.283
25	0106 25 00	36	41	64	14	0.396
28	0106 28 00	41	42	64	14	0.399

Brass Compression Fittings


0113 Equal Tube-to-Tube Connector with Mounting Boss

	Brass 	ØD		F	H	H1	L1	L/2	N	kg
		4	0113 04 00	10	10.5	7	9.5	19	6	0.022
		6	0113 06 00	13	13	9	10	20.5	7	0.033
		8	0113 08 00	14	14.5	9.5	11	23.5	8	0.041
		10	0113 10 00	19	19.5	12.5	11	26	9	0.082
		12	0113 12 00	22	22	14	12	26.5	11	0.107
		14	0113 14 00	24	25	16	11	28	12	0.122

0116 Equal Bulkhead Connector

	Brass 	ØD		F	F1	F2	L max	L1 max	L2	L3	ØT min	kg
		4	0116 04 00	10	10	13	27	17	7	17	8.3	0.024
		5	0116 05 00	13	12	14	28	18	7.5	17.5	10.3	0.035
		6	0116 06 00	13	13	14	28	19	7.5	17.5	10.3	0.037
		8	0116 08 00	14	14	17	29	20	7	17	12.3	0.045
		10	0116 10 00	19	19	22	33	25	9	19	16.5	0.101
		12	0116 12 00	22	22	22	33	25	9	19	18.5	0.121
		14	0116 14 00	24	24	24	35	25	8	18	20.5	0.145
		15	0116 15 00	24	24	24	35	25	8	18	20.5	0.134
		16	0116 16 00	27	27	27	36	28	9.5	19.5	22.5	0.189
		18	0116 18 00	27	30	30	40	30	10.5	20.5	24.5	0.237
		20	0116 20 00	32	30	32	41	31	11	21	27.5	0.274
		22	0116 22 00	36	36	36	42	32	11	21	30.5	0.372
		25	0116 25 00	36	41	38	46	36	11	21	33.5	0.469

0102 Equal Elbow

	Brass 	ØD		F	J	L max	kg
		4	0102 04 00	10	5	19	0.016
		5	0102 05 00	12	8	21	0.024
		6	0102 06 00	13	8	22	0.027
		8	0102 08 00	14	10	28	0.038
		10	0102 10 00	19	12	30	0.073
		12	0102 12 00	22	15	30	0.098
		14	0102 14 00	24	19	35	0.133
		15	0102 15 00	24	19	35	0.122
		16	0102 16 00	27	19	39	0.164
		18	0102 18 00	30	23	41	0.231
		20	0102 20 00	32	23	42	0.233
		22	0102 22 00	36	27	50	0.371
		25	0102 25 00	41	27	54	0.446
		28	0102 28 00	42	32	54.5	0.478


Brass Compression Fittings

0104

Equal Tee



Brass




ØD		F	H	J	L/2	kg
4	0104 04 00	10	9.5	8	19	0.028
5	0104 05 00	12	11	8	21	0.036
6	0104 06 00	13	11	8	22	0.040
8	0104 08 00	14	15	10	28	0.055
10	0104 10 00	19	14.5	12	30	0.105
12	0104 12 00	22	15	15	30	0.142
14	0104 14 00	24	18	19	35	0.190
15	0104 15 00	24	18	19	35	0.175
16	0104 16 00	27	21	19	39	0.239
18	0104 18 00	30	21.5	23	41	0.330
20	0104 20 00	32	21.5	23	42	0.330
22	0104 22 00	36	29	27	50	0.518
25	0104 25 00	41	29	27	54	0.630
28	0104 28 00	42	30	32	55	0.660

0142

Equal Y Piece with Mounting Boss



Brass




ØD		F	H max	H1	L max	L1	ØT	Kg
4	0142 04 00	10	16.5	7	26.5	17	4.2	0.032
6	0142 06 00	13	19.5	8.5	28	17	4.2	0.049
8	0142 08 00	14	21	8	30	17	6.2	0.061
10	0142 10 00	19	24.5	9	37.5	22	6.2	0.128
12	0142 12 00	22	26	11	38	23	6.2	0.110
14	0142 14 00	24	28	11	41.5	24.5	6.2	0.201
15	0142 15 00	24	28	11	41.5	24.5	6.2	0.204
16	0142 16 00	27	30	12	43	25	6.2	0.252
18	0142 18 00	30	31.5	12	50.5	31	10.2	0.220
25	0142 25 00	41	39	14	59	34	10.2	0.728

0107

Equal Cross



Brass



ØD		F	H	J	L/2	Kg
4	0107 04 00	10	9.5	8	19	0.035
5	0107 05 00	12	11	8	21	0.047
6	0107 06 00	13	11	8	22	0.052
8	0107 08 00	14	15	11	28	0.073
10	0107 10 00	19	14.5	14	30	0.142
12	0107 12 00	22	15	15	35	0.096
14	0107 14 00	24	18	20	35	0.246
15	0107 15 00	24	18	20	35	0.227
16	0107 16 00	27	21	20	39	0.312
18	0107 18 00	30	21.5	25	41	0.426
20	0107 20 00	32	21.5	25	42	0.429
22	0107 22 00	36	29	27	50	0.676
25	0107 25 00	41	29	27	50	0.819

Complementary Brass Fittings

Reducers, Olives and Nuts

This innovative reducer system, using a full range of nuts and olives, enables **different diameters** of steel, copper, brass or polymer tubes to be fitted onto **a single Parker Legris compression fitting**.

Product Advantages

Efficient Solution	Reduces envelope dimensions
	Quick and easy to assemble, whatever the diameters and tube material
Multiple Combinations	Improved stock management
	Silicone-free
Multiple Combinations	A single connector for up to 4 different tube materials and sizes
	Example: • polymer tube 4 mm O.D. • copper tube 8 mm O.D. • brass tube 12 mm O.D. • braided PVC hose 12 mm I.D.
A full range of olives and nuts to optimise all assembly operations	



- Applications
- Pneumatics
 - Cooling
 - Automotive Process
 - Lubrication
 - Fluid Transmission
 - Packaging
 - Industrial Machinery

Regulations

DI: 97/23/EC (PED)
 RG: 1907/2006 (REACH)
 DI: 2002/95/EC (RoHS)
 DI: 94/9/EC (ATEX)

Reducer Assembly Procedure

Operation	Assembly Sequence	Assembled Fitting
1 Assemble the reducer Place the reducer in the fitting body.	1 	
2 Assemble the nut and olive Place the nut and then the olive onto the tube.	2 	
3 Assemble the nut Push the tubing into the fitting until it butts against the tube reducer. Tighten the nut to the recommended torque (see opposite page).	3 	

Complementary Brass Fittings

Assembly Configuration

The table and information given below illustrate the large number of options available with Parker Legris brass compression fittings. To these must be added the advantages specific to the original Parker Legris reducer shown on the previous page.



Brass Body

0110 Brass 			0110..60 Brass 		0110..40 Steel 	0110..70* Polymer 
0124 Brass		0111 BNA** Brass	0124 Brass	0111 BNA** Brass	0124...40 Steel	
No olive required to assemble the plug						No olive required to assemble the tube
Brass plug: 0126	Copper, cold-rolled brass, polymer tube and barb connectors 0122 and 0165	Coiled annealed copper tube	Cold-rolled copper tube for vibration and side loading, etc.	Coiled annealed copper tube for vibration and side loading, etc.	Steel or copper tube: low/medium hydraulic pressure, lubricate before assembly	Polymer tube
						

*Assembly specifications for nut-olive 0110 ..70

This part functions as both olive and nut for flexible polymer tube assemblies:

1. Hand tighten the polymer nut-olive a few turns onto the body of the fitting; the knurling makes this easier.
2. Then introduce the polymer tube and push home into the body of the fitting.
3. Continue manually tightening the polymer nut-olive.
4. Finish tightening using a spanner until the nut body disengages and turns freely, which acts as a torque limiter.

N.B.: To avoid damaging the threads, do not insert the tube before hand tightening the nut-olive into the body of the fitting.


****Bureau de Normalisation de l'Automobile** (French Automotive Bureau of Standards)

Recommended Tightening Torque


Tightening torque in daN.m =

maximum tightening torque of a **0110** nut and **0124** olive with copper, brass or steel tube.

Nut **0110** and **0110..40**



Nut **0110..60**



Ø D (mm)	ØF 0110	ØF 0110..60	max. daN.m copper or brass	ØF 0110..40	max. daN.m steel
4	10	11	0.7	10	1.5
5	12	13	0.7	12	1.5
6	13	13	1.5	13	2.5
8	14	16	1.5	14	2.5
10	19	20	1.8	19	3
12	22	22	3	22	4.5
14	24	24	3.5	24	5.5
15	24	24	4	24	6
16	27	27	5	27	7
18	30	30	6	30	9
20	32	32	6	32	10
22	36	36	7	36	12
25	41	41	8	41	13
28	42		9		


Complementary Brass Compression Fittings

0166

3-Piece Reducer



Brass



ØD1	ØD2		F	kg
4	5	0166 04 05	13	0.011
	6	0166 04 06	13	0.011
	8	0166 04 08	14	0.012
	10	0166 04 10	19	0.031
	12	0166 04 12	22	0.044
	14	0166 04 14	24	0.054
5	15	0166 04 15	24	0.056
	6	0166 05 06	13	0.010
	8	0166 05 08	14	0.012
	10	0166 05 10	19	0.030
	12	0166 05 12	22	0.044
	14	0166 05 14	24	0.053
6	16	0166 05 16	27	0.078
	8	0166 06 08	14	0.012
	10	0166 06 10	19	0.030
	12	0166 06 12	22	0.043
	14	0166 06 14	24	0.052
	15	0166 06 15	24	0.054
8	16	0166 06 16	27	0.077
	10	0166 08 10	19	0.027
	12	0166 08 12	22	0.040
	14	0166 08 14	24	0.051
	15	0166 08 15	24	0.053
	16	0166 08 16	27	0.076
10	18	0166 08 18	30	0.100
	12	0166 10 12	22	0.037
	14	0166 10 14	24	0.045
	15	0166 10 15	24	0.047
	16	0166 10 16	27	0.068
	18	0166 10 18	30	0.095
12	20	0166 10 20	32	0.107
	22	0166 10 22	36	0.144
	25	0166 10 25	41	0.209
	14	0166 12 14	24	0.043
	15	0166 12 15	24	0.043
	16	0166 12 16	27	0.066
14	18	0166 12 18	30	0.092
	20	0166 12 20	32	0.102
	22	0166 12 22	36	0.140
	25	0166 12 25	41	0.200
	16	0166 14 16	27	0.060
	18	0166 14 18	30	0.084
15	20	0166 14 20	32	0.095
	22	0166 14 22	36	0.133
	25	0166 14 25	41	0.189
	18	0166 15 18	30	0.081
16	22	0166 15 22	36	0.130
	18	0166 16 18	30	0.078
	20	0166 16 20	32	0.088
	22	0166 16 22	36	0.126
18	25	0166 16 25	41	0.185
	20	0166 18 20	32	0.082
	22	0166 18 22	36	0.118
	25	0166 18 25	41	0.180
20	28	0166 18 28	42	0.176
	20	0166 20 25	41	0.168
	22	0166 22 28	42	0.168

ØD1: tube to be fitted


ØD2: for an x mm Ø fitting

Each of the above part numbers comprises:


- a reduction piece
- an olive, PN 0124
- a sleeve nut

Complementary Brass Compression Fittings


0124 Brass Olive

	Brass		ØD		kg
			4	0124 04 00	0.001
			5	0124 05 00	0.001
			6	0124 06 00	0.001
			8	0124 08 00	0.001
			10	0124 10 00	0.003
			12	0124 12 00	0.004
			14	0124 14 00	0.005
			15	0124 15 00	0.004
			16	0124 16 00	0.006
			18	0124 18 00	0.007
			20	0124 20 00	0.009
			22	0124 22 00	0.012
			25	0124 25 00	0.017
			28	0124 28 00	0.017

0124..40 Steel Olive

	Zinc-plated steel		ØD		kg
			4	0124 04 00 40	0.001
			6	0124 06 00 40	0.001
			8	0124 08 00 40	0.001
			10	0124 10 00 40	0.003
			12	0124 12 00 40	0.003
			14	0124 14 00 40	0.005
			15	0124 15 00 40	0.004
			16	0124 16 00 40	0.006
			18	0124 18 00 40	0.007
			20	0124 20 00 40	0.007
			22	0124 22 00 40	0.010
			25	0124 25 00 40	0.014


0111 BNA* Brass Olive

	Brass		ØD		kg
			4	0111 04 00	0.001
			5	0111 05 00	0.001
			6	0111 06 00	0.001
			8	0111 08 00	0.001
			10	0111 10 00	0.002
			12	0111 12 00	0.002
			14	0111 14 00	0.003
			15	0111 15 00	0.003
			16	0111 16 00	0.003


*BNA: Bureau de Normalisation de l'Automobile (standards organization in the field of Automotive Process)

Complementary Brass Compression Fittings


0110 Brass Nut

	Brass	ØD	C		F	L	kg
		4	M8x1	0110 04 00	10	11	0.005
		5	M10x1	0110 05 00	12	11	0.006
		6	M10x1	0110 06 00	13	11	0.008
		8	M12x1	0110 08 00	14	13	0.008
		10	M16x1.5	0110 10 00	19	15	0.019
		12	M18x1.5	0110 12 00	22	15	0.026
		14	M20x1.5	0110 14 00	24	15	0.029
		15	M20x1.5	0110 15 00	24	15	0.028
		16	M22x1.5	0110 16 00	27	17	0.042
		18	M24x1.5	0110 18 00	30	18	0.057
		20	M27x1.5	0110 20 00	32	18	0.057
		22	M30x1.5	0110 22 00	36	19	0.078
		25	M33x1.5	0110 25 00	41	21	0.121
		28	M36x1.5	0110 28 00	42	21	0.110


0110..40 Steel Nut

	Zinc-plated steel	ØD	C		F	L	kg
		4	M8x1	0110 04 00 40	10	11	0.004
		5	M10x1	0110 05 00 40	12	11.5	0.005
		6	M10x1	0110 06 00 40	13	12	0.008
		8	M12x1	0110 08 00 40	14	13.5	0.008
		10	M16x1.5	0110 10 00 40	19	16	0.018
		12	M18x1.5	0110 12 00 40	22	16.5	0.027
		14	M20x1.5	0110 14 00 40	24	17	0.030
		15	M20x1.5	0110 15 00 40	24	17	0.029
		16	M22x1.5	0110 16 00 40	27	18	0.042
		18	M24x1.5	0110 18 00 40	30	19	0.056
		20	M27x1.5	0110 20 00 40	32	20.5	0.061
		22	M30x1.5	0110 22 00 40	36	21.5	0.085

0110..60 Brass Long Nut

	Brass	ØD	C		F	L	kg
		4	M8x1	0110 04 00 60	11	14.5	0.007
		5	M10x1	0110 05 00 60	13	17	0.008
		6	M10x1	0110 06 00 60	13	17.5	0.011
		8	M12x1	0110 08 00 60	16	20	0.019
		10	M16x1.5	0110 10 00 60	20	23	0.032
		12	M18x1.5	0110 12 00 60	22	25	0.039
		14	M20x1.5	0110 14 00 60	24	30	0.051
		15	M20x1.5	0110 15 00 60	24	30	0.049
		16	M22x1.5	0110 16 00 60	27	32	0.070
		18	M24x1.5	0110 18 00 60	30	35	0.098
		20	M27x1.5	0110 20 00 60	32	35	0.102
		22	M30x1.5	0110 22 00 60	36	36	0.129

0110..70 Technical Polymer Nut-Olive

	Technical polymer	ØD	C		F	L	kg
		4	M8x1	0110 04 00 70	8	13	0.008
		6	M10x1	0110 06 00 70	11	15	0.002
		8	M12x1	0110 08 00 70	13	16	0.002
		10	M16x1.5	0110 10 00 70	17	19	0.004
		12	M18x1.5	0110 12 00 70	19	19	0.005
		14	M20x1.5	0110 14 00 70	22	20	0.005
		16	M22x1.5	0110 16 00 70	24	21	0.008

NB: polymer nut-olives should not be used on metal tubing.



Self-Fastening Barb Connectors for NBR Hose

This range of fittings is designed to meet the requirements of the automotive and robotics industries, combining as it does **optimum CNOMO manufacturing quality**, simple installation, reliable operation and a **long service life**.

Product Advantages

Perfect for Self-Fastening NBR Hose

- Quick and simple to install
- Compatible with the Parker Legris range of brass compression fittings
- Mechanical properties proven for use in industrial robotic installations
- Spark-resistant

Ergonomic and Time-Saving

- Fitting does not require lubrication or clamping, reducing assembly time
- Visual stop confirms installation is correct and improves operating safety
- Removal by cutting the tube
- The fitting can be re-used if necessary



Applications


- Welding Robots
- Pneumatics
- Compressed Air Systems
- Automotive Process
- Cooling

Technical Characteristics

Compatible Fluids	Coolants, compressed air						
Working Pressure	0 to 16 bar						
Working Temperature	0°C to +100°C (water) -20°C to +70°C (air)						
Tightening Torque, Type 0132	DN	6	8	10	14	18	22
	daN.m	0.7	1.5	1.8	3.5	6	7

Reliable performance is dependent upon the type of fluid conveyed and hose being used.

Component Materials



Silicone-free

Self-Fastening Hose Assembly Machine

Machine designed to assemble a barb connector and a self-fastening NBR hose.


Machine part number:
0650 00 00 05



Tube Cutting and Positioning

Cut the hose square and position the barb connector on the mounting tool.


Barb Connector Support



Press-Fitting the Tube

Activate the press-fit tool; connection is complete when the tube is fully home on the barb connector. This tool has been designed for use with 5 different diameters and is easy to operate.

Barb Connector Support




Regulations

Industrial

DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1907/2006 (REACH)
CNOMO: E07.21.115N


Self-Fastening Barb Connectors for NBR Hose

0132 Self-Fastening Barb Connector for Brass Compression Fitting

	Brass		ØD	ØD1	ØD2		F	G	L	L1	ØT	kg
			6	6.3	13	0132 06 56	12	16.5	32.5	12.5	4.8	0.010
			8	6.3	13	0132 08 56	14	16.5	29.5	11.5	4.8	0.015
			10	6.3	13	0132 10 56	19	16.5	30	14	4.8	0.028
				9.5	16	0132 10 60	19	19.5	34	14	7.5	0.030
			14	9.5	16	0132 14 60	24	19.5	35.5	15	7.5	0.050
				12.7	19	0132 14 62	24	23.5	39.5	15	10	0.054
			18	12.7	19	0132 18 62	30	23.5	41.5	17	10	0.090
				15.9	23	0132 18 66	30	27	50	17	13.5	0.090
			22	19.1	27	0132 22 69	36	30.5	56.5	17	16	0.128

Polymer collar


0133..39 Self-Fastening Barb Connector with Bi-Material Seal, Male BSPP Thread

	Brass, zinc-plated steel with NBR seal		ØD1	ØD2	C		E	F	G	H	L	ØT	kg
			6.3	13	G1/8	0133 56 10 39	5.5	13	14	20	31.5	4.8	0.012
				13	G1/4	0133 56 13 39	7	17	17	20	33.5	4.8	0.018
			9.5	16	G1/4	0133 60 13 39	7	17	17	24	37.5	7.5	0.022
				16	G3/8	0133 60 17 39	9.5	22	22	24	42.5	7.5	0.038
			12.7	19	G3/8	0133 62 17 39	9.5	22	22	28	46.5	10	0.045
				19	G1/2	0133 62 21 39	10.5	27	26	28	48.5	10	0.060
			15.9	23	G1/2	0133 66 21 39	10.5	27	26	36.5	57	13.5	0.064
				23	G3/4	0133 66 27 39	11.5	32	32	36.5	59	13.5	0.095
			19.1	27	G3/4	0133 69 27 39	11.5	32	32	43	65.5	16	0.111

Thread with bi-material seal and polymer collar.

Bi-material sealing washer part number 0139 can be found in Chapter 9.

0134 Self-Fastening Barb Connector, Male BSPT Thread

	Brass		ØD1	ØD2	C		F	G	L	L1	ØT	kg
			6.3	13	R1/8	0134 56 10	14	16.5	32.5	20	4.8	0.015
				13	R1/4	0134 56 13	14	16.5	37	20	4.8	0.020
			9.5	16	R1/4	0134 60 13	14	19.5	41	24	7.5	0.022
				16	R3/8	0134 60 17	19	19.5	41.5	24	7.5	0.036
			12.7	19	R3/8	0134 62 17	19	23.5	45.5	28	10	0.038
				19	R1/2	0134 62 21	22	23.5	50	28	10	0.062
			15.9	23	R1/2	0134 66 21	22	27	58.5	36.5	13.5	0.056
				23	R3/4	0134 66 27	27	27	60.5	36.5	13.5	0.101
			19.1	27	R3/4	0134 69 27	27	30.5	67	43	16	0.108

Polymer collar

Self-fastening NBR hose is selected by nominal diameter; for example:

Barb Connector	O.D. (Tube)	Ø DN (Tube)	Self-Fastening NBR hose
0132 10 56	10	1/4	10..H 56...




Brass Adaptors

0122

Barb Connector for Hose



Brass




ØD1	ØD2		ØD3	L	L1	ØT min	kg
4	4	0122 04 04	6	37.5	22.5	3	0.004
5	4	0122 05 04	6	37.5	22.5	3	0.003
6	4	0122 06 04	6	37.5	22.5	3	0.005
	7	0122 06 07	9	37.5	22.5	6	0.007
8	6	0122 08 06	8	40	22.5	5	0.007
	7	0122 08 07	9	40	22.5	6	0.008
	10	0122 08 10	12.5	40	22.5	9	0.013
10	7	0122 10 07	9	43	22.5	6	0.010
	10	0122 10 10	12.5	43	22.5	9	0.014
12	10	0122 12 10	12.5	43	22.5	9	0.014
	13	0122 12 13	15	50	29.5	12	0.018
14	13	0122 14 13	15	52	29.5	12	0.019
	16	0122 14 16	18.5	60.5	38	15	0.308
15	13	0122 15 13	15	52	29.5	12	0.019
	16	0122 15 16	18.5	60.5	38	15	0.032
16	13	0122 16 13	15	53.5	29.5	12	0.021
	16	0122 16 16	18.5	62	38	15	0.032
18	16	0122 18 16	18.5	62	38	15	0.032
	19	0122 18 19	21.5	62	38	18	0.041
20	16	0122 20 16	18.5	64	38	15	0.034
	19	0122 20 19	21.5	64	38	18	0.038
22	19	0122 22 19	21.5	64	38	18	0.039
	19	0122 25 19	21.5	70	38	18	0.049
25	25	0122 25 25	27.5	70	38	24	0.054
28	25	0122 28 25	27.5	70	38	24	0.087

0165

Barb Connector for Flexible Tubing




Brass



ØD1	ØD2		ØD3	L	L1	ØT min	kg
4	4	0165 04 06	4.3	30	15	2	0.002
5	4	0165 05 06	4.3	30	15	2	0.010
6	4	0165 06 06	4.3	30	15	2	0.003
	6	0165 06 08	6.4	30	15	4	0.004
	8	0165 06 10	8.4	30	15	4	0.004
8	6	0165 08 08	6.4	32.5	15	4	0.006
	8	0165 08 10	8.4	32.5	15	6	0.006
	10	0165 08 12	10.7	37.5	20	8	0.009
10	8	0165 10 10	8.4	35.5	15	6	0.008
	10	0165 10 12	10.7	40.5	20	8	0.010
	12	0165 10 14	12.7	40.5	20	8	0.012
12	10	0165 12 12	10.7	40.5	20	8	0.011
	12	0165 12 14	12.7	40.5	20	10	0.013
14	12	0165 14 14	12.7	42.5	20	10	0.014
15	13	0165 15 16	13.7	42.5	20	11	0.016
16	13	0165 16 16	13.7	44	20	11	0.018


Assembly: Barb Connectors

Our barb connectors 0122 and 0165 are designed to be used with different types of hose. They are secured using the nut and olive provided with the fitting.




Brass Adaptors

0126 Plug for Compression Fitting

	Brass		ØD		L	kg
			4	0126 04 00	10	0.001
			5	0126 05 00	10	0.003
			6	0126 06 00	10	0.003
			8	0126 08 00	11.5	0.006
			10	0126 10 00	13	0.010
			12	0126 12 00	13	0.014
			14	0126 14 00	13.5	0.020
			15	0126 15 00	13.5	0.022
			16	0126 16 00	16	0.029
			18	0126 18 00	16	0.039
			20	0126 20 00	16	0.045
			22	0126 22 00	18	0.003
			28	0126 28 00	19.5	0.108


The plug is used to blank off an outlet in a compression fitting, replacing the olive.
When an open outlet is required, simply dismantle and replace the plug with the tube olive, reusing the nut.
The plug is also reusable.

0125 Tube End Plug for Compression Fitting

	Brass		ØD	C		F	L	L1	kg
			4	M8x1	0125 04 00	10	12	8	0.006
			6	M10x1	0125 06 00	11	13.5	9.5	0.008
			8	M12x1	0125 08 00	14	14	9	0.013
			10	M16x1.5	0125 10 00	17	18	11	0.025
			12	M18x1.5	0125 12 00	19	18	11	0.030
			14	M20x1.5	0125 14 00	22	19	11	0.041


This plug enables unused tubes to be blanked off.
The male thread on the plug has the same pitch as the female thread on the sleeve nut of a standard Parker Legris fitting.
Therefore the plug screwed into the sleeve nut blanks off the tube.
To reopen the passage, simply unscrew the plug and fit the required coupler.
No further treatment of the tube is required.

0220 Hex Head Plug with Captive Sealing Washer, Male BSPP and Metric Thread

	Brass, technical polymer		C		F	G	H	kg
			M5x0.8	0220 19 00	8	8	5	0.002
			G1/8	0220 10 00	14	14	7.5	0.011
			G1/4	0220 13 00	17	17	7.5	0.019
			G3/8	0220 17 00	17	22	8.5	0.024
			G1/2	0220 21 00	22	27	10	0.040

Thread with pre-assembled washer.
M5: with screwdriver slot for tightening.
Maximum allowable working pressure = 20 bar.
Part number with suffix 99, maximum allowable working pressure = 250 bar, example: 0220 19 00 99.
Conforms to BNA 229 (with the exception of M5 model): BSPP thread, ISO ISO 228-1;
metric thread, ISO NFE 03-054.

0220..39 Hex Head Plug with Bi-Material Seal, Male BSPP Thread

	Brass, zinc-plated steel with NBR seal		C		F	G	H1	kg
			G1/8	0220 10 00 39	14	14	6.5	0.012
			G1/4	0220 13 00 39	17	17	6.5	0.020
			G3/8	0220 17 00 39	17	22	8	0.025
			G1/2	0220 21 00 39	22	26	9	0.043
			G3/4	0220 27 00 39	22	32	10	0.060
			G1	0220 34 00 39	27	39.5	10.5	0.089

Plug with bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.


Brass Adaptors

0120

Stud Standpipe, Male BSPT Thread



Brass




ØD	C		F	L	L1	kg
4	R1/8	0120 04 10	11	25.5	14	0.007
5	R1/8	0120 05 10	11	26	14.5	0.007
6	R1/8	0120 06 10	11	26.5	15	0.008
	R1/4	0120 06 13	14	31	15	0.015
8	R1/8	0120 08 10	11	28.5	17	0.009
	R1/4	0120 08 13	14	33	17	0.016
10	R3/8	0120 08 17	17	33.5	17	0.020
	R1/4	0120 10 13	14	36	20	0.018
12	R3/8	0120 10 17	17	36.5	20	0.022
	R1/2	0120 10 21	22	41	20	0.038
14	R1/4	0120 12 13	14	36	20	0.018
	R3/8	0120 12 17	17	36.5	20	0.022
16	R1/2	0120 12 21	22	41	20	0.041
	R3/8	0120 14 17	17	38	21.5	0.024
18	R1/2	0120 14 21	22	42.5	21.5	0.041
	R3/8	0120 15 17	17	38	21.5	0.023
20	R1/2	0120 15 21	22	42.5	21.5	0.041
	R3/8	0120 16 17	17	39.5	23	0.024
22	R1/2	0120 16 21	22	44	23	0.042
	R1/2	0120 18 21	22	44.5	23.5	0.042
24	R3/4	0120 18 27	27	47.5	23.5	0.071
	R3/4	0120 20 27	27	49	25	0.071
26	R3/4	0120 22 27	27	48.5	25.5	0.067
	R1	0120 22 34	36	52.5	25.5	0.116
28	R1	0120 25 34	36	57	30	0.119
30	R1	0120 28 34	36	57	30	0.138

0112

Sleeve Nut for Compression Fitting, Male Metric Thread



Brass




ØD	C		E	F	L	kg
4	M8x1	0112 04 00	7	10	13	0.005
5	M10x1	0112 05 00	7.5	11	13.5	0.007
6	M10x1	0112 06 00	7.5	11	13.5	0.006
8	M12x1	0112 08 00	8	13	15	0.008
10	M16x1.5	0112 10 00	11	17	18	0.018
12	M18x1.5	0112 12 00	11	19	18	0.021
14	M20x1.5	0112 14 00	11	22	18	0.026

This product was designed to allow the tube to be fitted directly into the tapped port in a body using a standard Parker Legris olive.
For the corresponding drawings (cavity for Parker Legris olive), please consult us.


Brass Adaptors

0128..39 Stud Standpipe with Bi-Material Seal, Male BSPP Thread

	Brass, zinc-plated steel with NBR seal						E	F	H	Kg
			ØD	C						
			4	G1/8	0128 04 10 39		7.5	13	20	0.009
				G1/4	0128 04 13 39		9	17	22	0.015
			6	G1/8	0128 06 10 39		7.5	13	21	0.010
				G1/4	0128 06 13 39		9	17	23	0.016
			8	G1/8	0128 08 10 39		7.5	13	23	0.011
				G1/4	0128 08 13 39		9	17	25	0.017
				G3/8	0128 08 17 39		12	22	26	0.033
				G1/4	0128 10 13 39		9	17	28	0.018
			10	G3/8	0128 10 17 39		12	22	29	0.034
				G1/2	0128 10 21 39		27	27	30	0.048
			14	G3/8	0128 14 17 39		12	22	30.5	0.035
				G1/2	0128 14 21 39		27	27	31.5	0.049
			18	G1/2	0128 18 21 39		27	27	33.5	0.052
				G3/4	0128 18 27 39		14	32	34.5	0.084
			22	G3/4	0128 22 27 39		14	32	36.5	0.082
				G1	0128 22 34 39		16.5	41	38	0.123
			28	G1	0128 28 34 39		16.5	41	42.5	0.149


With bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.

0151..39 Straight Male Orientable Adaptor, with Bi-Material Seal, Male BSPP Thread

	Brass, NBR, zinc-plated steel with NBR seal						E	E1	F	F1	H	H1	kg
			C										
			G1/8		0151 10 10 39		5.5	7	13	14	6	6.5	0.017
				G1/4	0151 13 13 39		7	8.5	17	19	6.5	9	0.036
			G3/8		0151 17 17 39		9.5	9.5	22	22	9	9	0.057
				G1/2	0151 21 21 39		10.5	10.5	27	27	10	10	0.083
			G3/4		0151 27 27 39		11.5	11.5	32	32	11	10	0.121
				G1	0151 34 34 39		13	13.5	41	41	12.5	10.5	0.230

With bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.

0168..39 Reducer, with Bi-Material Seal, Male BSPP Thread/Female BSPP and Metric Thread


	Brass, zinc-plated steel with NBR seal						E	F	H	kg
			C1	C2						
			G1/8	M5x0.8	0168 10 19 39		8	14	4.5	0.009
				M5x0.8	0168 13 19 39		8	17	5	0.018
			G1/4	G1/8	0168 13 10 39		8	17	5	0.012
				G1/8	0168 17 10 39		10	19	5	0.020
			G3/8	G1/4	0168 17 13 39		10	19	5	0.013
				G1/8	0168 21 10 39		12	24	7.5	0.052
			G1/2	G1/4	0168 21 13 39		12	24	7.5	0.043
				G3/8	0168 21 17 39		12	24	7.5	0.030
			G3/4	G1/4	0168 27 13 39		12	32	9.5	0.099
				G3/8	0168 27 17 39		12	32	9.5	0.086
				G1/2	0168 27 21 39		12	32	9.5	0.065

With bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.

Brass Adaptors

0127

Tube Support for Polymer Tubing

	Brass 	ØD1	ØD2		L	kg
		4	2	0127 04 00	11	0.001
			2.7	0127 04 27	11	0.001
		5	3	0127 05 03	11	0.001
			3.3	0127 05 00	11.5	0.009
		6	4	0127 06 00	11.5	0.001
		8	5.5	0127 08 55	14	0.001
			6	0127 08 00	14	0.001
			7	0127 10 07	18	0.001
		10	7.5	0127 10 75	18	0.001
			8	0127 10 00	18	0.002
			8	0127 12 08	18	0.002
		12	9	0127 12 09	18	0.002
			10	0127 12 00	18	0.001
		14	11	0127 14 11	18	0.002
			12	0127 14 00	18	0.002
		15	12	0127 15 12	18	0.002
		16	13	0127 16 13	18	0.003
		18	14	0127 18 14	19.5	0.003
		20	15	0127 20 15	20.5	0.003
		22	16	0127 22 16	21	0.004
		25	19	0127 25 19	25	0.007
		This tube support guarantees good gripping, at high temperatures and pressures, by preventing collapsing of the tube.				

Stainless Steel Compression Fitting Range

Stainless Steel Fittings

Stud Fittings

1805 BSPT Page 5-34	1805 NPT Page 5-34	1814 BSPP Page 5-34	1809 BSPT Page 5-35	1809 NPT Page 5-35	1820 BSPT Page 5-35	1820 NPT Page 5-35
						

Tube-to-Tube Fittings

1806 Page 5-36	1816 Page 5-36	1802 Page 5-36	1804 Page 5-36
			

Complementary Fittings

1866 Page 5-39	1824 Page 5-39	1810 Page 5-39
		

Accessories

1822 Page 5-39	1827 Page 5-39
	

Stainless Steel Compression Fittings

Manufactured in 316L stainless steel, these fittings combine all the advantages of the "universal" compression fitting with **excellent resistance** to environmental conditions and **corrosive fluids**. They are pressure and temperature-resistant and are able to withstand strong vibration and water hammer.

Product Advantages

For Use in Many Environments

Manufactured in 316L stainless steel
Suitable for all environments and fluids
Resistant to water hammer and vibration
Excellent sealing and retention of the tube
Suitable for pneumatic and medium pressure hydraulic applications
Metallic sealing guarantees maximum service life

Many Tube Options

Possibility of easily connecting different tube materials and diameters to the same fitting body
No tube support required for rigid and semi-rigid polyamide tubing below 12 mm



Applications

- Food Process
- Fluid Transmission
- Pneumatics
- Automotive Process
- Petrochemical
- Chemical
- Offshore Oil & Gas


Technical Characteristics

Compatible Fluids	Many fluids				
Working Pressure	Vacuum to 400 bar (80 bar in corrosive environments)				
Working Temperature	-40°C to +250°C				

Tightening Torques	DN	6	8	10	12	16
	daN.m	2	3	4	6.5	9.5

Reliable performance is dependent upon the type of fluid conveyed and tubing being used. Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Maximum Bore Diameters

The table below shows the recommended compatibility of tube size, BSPP male thread and maximum bore.

Tube O.D	BSPP Thread	Max. Bore
6	G1/8	4
6-8-10	G1/4	7
10-12	G3/8	11
16	G1/2	14

Tube Length for Assembly

Minimum length of tube (L) between 2 fittings.



ØD	L mm	ØD	L mm
4	26.5	10	39
6	26	12	39
8	32	16	46.5

Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
DI: 97/23/EC (PED)
RG: 1935/2004
RG: 1907/2006 (REACH)
DI: 94/09/EC (ATEX)
FDA: 21 CFR 177.1550
NACE MR0175: compatible materials
ISO 15156-1/-2/-3: compatible materials


Stainless Steel Compression Fittings

Installation

Fitting

The fitting comprises three parts (body/olive/nut). For assembly procedure, please see Brass Compression Fitting page.

Diagram: Assembled Fitting




A very slight distortion of the tube appears; this shows the fitting has been correctly tightened.

Orientable Elbow Assembly


Elbow
1802

Adaptor
1820



Customised Fittings

If our standard range does not meet your needs, Parker Legris can develop customised solutions for your applications.



Technical Characteristics

The use of Parker Legris stainless steel compression fittings is dependant on the tube material. Tables of recommended working pressure for the different tubes are shown below.

Recommended Tube Type

Semi-rigid polyamide or fluoropolymer tube

Stainless steel tube

"Thin Wall" cold-drawn seamless, annealed and passivated:
wall thickness tolerance ± 0.1 mm.
For use with "thin wall" stainless steel tube from 6 mm to 16 mm O.D.,
maximum wall thickness 1 mm.

Recommended Tube/Fitting Assembly Configurations


Assembled using Parker Legris olive and nut in stainless steel, with a tube support.

Stainless steel tube

Stainless steel tube: in cold-rolled straight lengths
Coiled annealed stainless tube: reduces working pressure by 35%; do not use if there is vibration.


Semi-Rigid Polyamide Tube

Maximum Working Pressure (bar)



Stainless Steel Tube

Maximum Working Pressure (bar)



Working Pressure Coefficients for Semi-Rigid Tubing

Temperature °C	-40°C / -15°C	-15°C / +30°C	+30°C / +50°C	+50°C / +70°C	+70°C / +100°C
Factor	1.8	1	0.68	0.55	0.31

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.


Stainless Steel Compression Fittings

1805

Stud Fitting, Male BSPT Thread



Stainless steel 316L




ØD	C		F	F1	H _{max}	H1	kg
6	R1/8	1805 06 10	12	13	19.5	7.5	0.017
	R1/4	1805 06 13	14	13	19.5	7.5	0.025
8	R1/8	1805 08 10	13	14	21	7	0.019
	R1/4	1805 08 13	14	14	21	7	0.024
10	R1/4	1805 10 13	17	19	25.5	9	0.044
	R3/8	1805 10 17	17	19	25.5	9	0.049
	R1/2	1805 10 21	22	19	26.5	10	0.076
12	R1/4	1805 12 13	19	22	26	9	0.054
	R3/8	1805 12 17	19	22	26	9	0.058
	R1/2	1805 12 21	22	22	27	10	0.081
16	R3/8	1805 16 17	24	27	28.5	9.5	0.086
	R1/2	1805 16 21	24	27	28.5	9.5	0.094

1805

Stud Fitting, Male NPT Thread



Stainless steel 316L



ØD	C		F	F1	H _{max}	H1	kg
6	NPT1/8	1805 06 11	12	13	19.5	7.5	0.018
	NPT1/4	1805 06 14	14	13	19.5	7.5	0.027
	NPT3/8	1805 06 18	19	13	20.5	8.5	0.033
	NPT1/2	1805 06 22	22	13	21.5	9.5	0.049
8	NPT1/8	1805 08 11	13	14	21	7	0.020
	NPT1/4	1805 08 14	14	14	21	7	0.027
10	NPT1/4	1805 10 14	17	19	25.5	9	0.045
	NPT3/8	1805 10 18	19	19	25.5	9	0.055
	NPT1/2	1805 10 22	22	19	26.5	10	0.083
12	NPT1/4	1805 12 14	19	22	26	9	0.056
	NPT3/8	1805 12 18	19	22	26	9	0.061
	NPT1/2	1805 12 22	22	22	27	10	0.087
16	NPT3/8	1805 16 18	24	27	28.5	9.5	0.087
	NPT1/2	1805 16 22	24	27	28.5	9.5	0.097

1814

Stud Fitting, Female BSPP Thread

ØD	C		E	F	F1	H _{max}	H1	kg
6	G1/8	1814 06 10	7.5	14	13	29	17	0.023
	G1/4	1814 06 13	11	17	13	29	21	0.032
8	G1/4	1814 08 13	11	17	14	34.5	20.5	0.033
	G3/8	1814 10 17	11.5	22	19	38.5	22	0.064
10	G1/2	1814 10 21	15	27	19	43	26.5	0.093
	G3/8	1814 12 17	11.5	22	22	39	22	0.072
12	G1/2	1814 12 21	15	27	22	43.5	26.5	0.100
	G1/2	1814 16 21	15	27	27	45	26	0.120

Stainless Steel Compression Fittings

1809

Stud Elbow, Male BSPT Thread

ØD	C		F	H	J	L _{max}	L1	kg
6	R1/8	1809 06 10	13	18	8	25.5	13.5	0.021
	R1/4	1809 06 13	13	23	10	25.5	13.5	0.030
8	R1/8	1809 08 10	14	20.5	10	28.5	14.5	0.027
	R1/4	1809 08 13	14	23	10	28.5	14.5	0.031
10	R1/4	1809 10 13	19	25	12	32.5	16	0.050
	R3/8	1809 10 17	19	25.5	12	32.5	16	0.058
12	R1/2	1809 12 21	19	32	18	36.5	20	0.091
	R1/4	1809 12 13	22	26	14	34	17	0.067
16	R3/8	1809 12 17	22	27	14	34	17	0.070
	R1/2	1809 12 21	22	32	18	37	20	0.098
	R3/8	1809 16 17	27	28.5	18	39.5	21	0.107
	R1/2	1809 16 21	27	31.5	18	39.5	21	0.114

1809

Stud Elbow, Male NPT Thread

ØD	C		F	H	J	L _{max}	L1	kg
6	NPT1/8	1809 06 11	13	19.5	8	25.5	13.5	0.022
	NPT1/4	1809 06 14	13	25.5	10	25.5	13.5	0.031
	NPT3/8	1809 06 18	13	28	12	27	15	0.046
	NPT1/2	1809 06 22	13	34	12	29	17	0.072
8	NPT1/8	1809 08 11	14	22	10	28.5	14.5	0.028
	NPT1/4	1809 08 14	14	25.5	10	28.5	14.5	0.033
10	NPT1/4	1809 10 14	19	27.5	12	32.5	16	0.052
	NPT3/8	1809 10 18	19	28	12	32.5	16	0.061
12	NPT1/2	1809 10 22	19	35	18	36.5	20	0.096
	NPT1/4	1809 12 14	22	28.5	14	34	17	0.069
16	NPT3/8	1809 12 18	22	29.5	14	34	17	0.074
	NPT1/2	1809 12 22	22	35	18	37	20	0.102
	NPT3/8	1809 16 18	27	31	18	39.5	21	0.110
	NPT1/2	1809 16 22	27	34.5	18	39.5	21	0.116

1820

Stud Standpipe, Male BSPT Thread

ØD	C		F	L	L1	kg
6	R1/8	1820 06 10	12	26.5	15	0.009
	R1/4	1820 06 13	14	31	15	0.017
8	R1/8	1820 08 10	12	28.5	17	0.008
	R1/4	1820 08 13	14	33	17	0.016
10	R1/4	1820 10 13	14	36	20	0.016
	R3/8	1820 10 17	17	36.5	20	0.025
12	R1/2	1820 10 21	22	41	20	0.052
	R1/4	1820 12 13	14	36	20	0.016
16	R3/8	1820 12 17	17	36.5	20	0.022
	R1/2	1820 12 21	22	41	20	0.048
	R3/8	1820 16 17	17	39.5	23	0.022
	R1/2	1820 16 21	22	44	23	0.038


1820

Stud Standpipe, Male NPT Thread


ØD	C		F	L	L1	kg
6	NPT1/8	1820 06 11	12	26.5	15	0.009
	NPT1/4	1820 06 14	14	31	15	0.019
8	NPT1/8	1820 08 11	12	28.5	17	0.009
	NPT1/4	1820 08 14	14	33	17	0.019
10	NPT1/4	1820 10 14	14	36	20	0.018
	NPT3/8	1820 10 18	19	36.5	20	0.032
12	NPT1/2	1820 10 22	22	41	20	0.060
	NPT1/4	1820 12 14	14	36	20	0.019
16	NPT3/8	1820 12 18	19	36.5	20	0.028
	NPT1/2	1820 12 22	22	41	20	0.053
	NPT3/8	1820 16 18	19	39.5	23	0.027
	NPT1/2	1820 16 22	22	44	23	0.042

Stainless Steel Compression Fittings


1806 Equal Tube-to-Tube Connector

	Stainless steel 316L				ØD		F	F1	L _{max}	L1	kg
					6	1806 06 00	12	13	34.5	11	0.025
					8	1806 08 00	13	14	38.5	10	0.029
					10	1806 10 00	17	19	46	13	0.066
					12	1806 12 00	19	22	47	13	0.085
					16	1806 16 00	24	27	51	13	0.135


1816 Equal Bulkhead Connector

	Stainless steel 316L				ØD		F	F1	L _{max}	L1 _{max}	L2	L3	ØT _{min}	kg
					6	1816 06 00	13	13	28	19	7.5	17	10.5	0.034
					8	1816 08 00	14	14	29	20	7	17	12.5	0.042
					10	1816 10 00	19	19	33	25	9	19	16.5	0.094
					12	1816 12 00	22	22	33	25	9	19	18.5	0.113
					16	1816 16 00	27	27	36	28	9.5	19.5	22.5	0.179

1802 Equal Elbow

	Stainless steel 316L				ØD		F	J	L _{max}	L1	kg
					6	1802 06 00	13	8	25.5	13.5	0.028
					8	1802 08 00	14	10	28.5	14.5	0.035
					10	1802 10 00	19	12	32.5	16	0.071
					12	1802 12 00	22	14	34	17	0.093
					16	1802 16 00	27	18	39.5	21	0.151

1804 Equal Tee

	Stainless steel 316L				ØD		F	J	L1	L/2	kg
					6	1804 06 00	13	8	13.5	25.5	0.040
					8	1804 08 00	14	10	14.5	28.5	0.050
					10	1804 10 00	19	12	16	32.5	0.103
					12	1804 12 00	22	14	17	34	0.133
					16	1804 16 00	27	18	21	39.5	0.214

Complementary Stainless Steel Fittings

Reducers, Olives and Nuts

This innovative reducer system, using a full range of nuts and olives, enables **different diameters** of stainless steel, fluoropolymer or polymer tubes to be fitted onto **a single Parker Legris compression fitting**.

Product Advantages

Efficient Solution

- Reduces envelope dimensions
- Quick and easy to assemble, whatever the diameters and tube material
- Improved stock management
- Silicone-free

Multiple Combinations

- A single connector for up to 3 different tube materials and sizes.
- Example:
 - Advanced PE tubing 6 mm O.D.
 - stainless steel tubing 8 mm O.D.
 - fluoropolymer tubing 12 mm O.D. or braided PVC hose 10 mm I.D.
- A full range of olives and nuts to optimise all assembly operations




Food Process
Fluid Transmission
Pneumatics
Automotive Process
Petrochemical
Cooling & Heating
Chemical
Offshore Oil & Gas

Applications

Reducer Assembly Procedure

Operation	Assembly Sequence	Assembled Fitting
1 Assemble the reducer Place the reducer in the fitting body.	1 	
2 Assemble the nut and olive Place the nut and then the olive onto the tube.	2 	
3 Assemble the nut Push the tube into the fitting until it bottoms on the reducer. Tighten the nut to the recommended torque (see opposite page).	3 	

Assembly: Barb Connectors



Regulations

DI: 2002/95/EC (RoHS), 2011/65/EC
 DI: 97/23/EC (PED)
 RG: 1935/2004
 RG: 1907/2006 (REACH)
 DI: 94/09/EC (ATEX)
 FDA: 21 CFR 177.1550
 NACE MR0175: compatible materials
 ISO 15156-1/-2/-3: compatible materials

Our barb connector 1822 is designed to be also used with different types of hose. It is secured using the nut and olive provided with the fitting.

Stainless Steel Compression Fittings

1866 3-Piece Reducer

Stainless steel 316L		ØD1	ØD2		F	kg
		6	8	1866 06 08	14	0.011
			10	1866 06 10	19	0.028
			12	1866 06 12	22	0.040
		8	10	1866 08 10	19	0.026
			12	1866 08 12	22	0.037
			16	1866 08 16	27	0.071
		10	12	1866 10 12	22	0.034
			16	1866 10 16	27	0.065
			12	1866 12 16	27	0.061

1824 Stainless Steel Olive

Stainless steel 316L	ØD		kg
	6	1824 06 00	0.001
	8	1824 08 00	0.001
	10	1824 10 00	0.003
	12	1824 12 00	0.004
	16	1824 16 00	0.005

1810 Stainless Steel Nut

Stainless steel 316L	ØD	C		F	L	kg
	6	M10x1	1810 06 00	13	11	0.007
	8	M12x1	1810 08 00	14	13	0.008
	10	M16x1.5	1810 10 00	19	15	0.017
	12	M18x1.5	1810 12 00	22	15	0.024
	16	M22x1.5	1810 16 00	27	17	0.041


1822 Barb Adaptor for Hose

Stainless steel 316L	ØD1	ØD2		ØD3	L	L1	ØT min	kg
	6	7	1822 06 07	9	37.5	22.5	6	0.006
		6	1822 08 06	8	40	22.5	5	0.007
	8	7	1822 08 07	9	40	22.5	6	0.007
		10	1822 08 10	12.5	40	22.5	9	0.011
	10	7	1822 10 07	9	43	22.5	6	0.009
		10	1822 10 10	12.5	43	22.5	9	0.013
	12	10	1822 12 10	12.2	43	22.5	9	0.012
		13	1822 12 13	15	50	29.5	13	0.016

1827 Stainless Steel Tube Support

Stainless steel 316L	ØD1	ØD2		L	kg
	6	4	1827 06 00	11.5	0.001
	8	6	1827 08 00	14	0.001
	10	8	1827 10 00	18	0.001
	12	9	1827 12 09	18	0.001
	12	10	1827 12 00	18	0.001
	16	14	1827 16 00	18	0.002

This tube support is necessary when using fluoropolymer tubing at all temperatures compatible with the fitting/tubing assembly.



PL Nickel-Plated Brass Spigot Fitting Range

PL Nickel-Plated Brass Spigot Fittings

Stud Fittings

FBPL NPT Page 5-43	F3BPL BSPT Page 5-43	F4BPL BSPP Page 5-43	F8BPL Metric Page 5-43	CBPL NPT Page 5-44	C3BPL BSPT Page 5-44
					
C4BPL BSPP Page 5-44	C8BPL Metric Page 5-44	RBPL NPT Page 5-45	R3BPL BSPT Page 5-45	SBPL NPT Page 5-45	S3BPL BSPT Page 5-45
					

Banjo Fitting

COR4BPL BSPP Page 5-45


Tube-to-Tube Fittings

HBPL Connector Page 5-46	JBPL Connector Page 5-46	WBPL Bulkhead Connector Page 5-46
		

Complementary Fitting

BPLM Nut Page 5-46


PL Nickel-Plated Brass Spigot Fittings

This range of Parker Legris has a sealing system which guarantees **excellent sealing and full flow**. PL fittings for flexible tubing are **fully re-usable**. They provide excellent compatibility with a wide variety of fluids.

Product Advantages

Rapid Assembly

Nut design allows hand tightening with soft tubing (PU, PE etc.)
Quick to assemble and disassemble
Compatible with all flexible tubes of hardness up to 90 shore A (polyurethane, polyamide, polyethylene, fluoropolymers, etc.)
Mechanical stop on the body to prevent overtightening

Performance

Special spigot design ensures full flow and excellent tensile performance
Reliable direct sealing system without the use of a seal or olive
Low and medium pressure
Nickel-plated for increased corrosion resistance



Applications

- Food Process
- Painting
- Pneumatic Systems
- Chemical
- Welding
- Laboratories
- Railway


Technical Characteristics

Compatible Fluids	Compressed air Other fluids: contact us
Working Pressure	Vacuum to 40 bar
Working Temperature	-40°C to +100°C

Tensile Performance (polyamide tubing)	Ø	2.7/4	4/6	6/8	7.5/10	8/10	10/12	11/14
	daN	11	41	52	88	67	79	149

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.
Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

Component Materials



Silicone-free

Installation

Cutting the Tube



Cut the polymer tube square.

Preparing the Connection



Slide the nut onto the tube.

Connecting the Tube



Push the tube home into the body of the fitting.

Final Assembly




Tighten the nut by hand (in the case of soft tubing) or using a spanner (for semi-rigid tubing) until it comes into contact with the end stop.

Stud Fittings


FBPL

Stud Fitting, Male NPT Thread

	Nickel-plated brass			ØD	C		F	F1	H	kg
				2.7x4	NPT1/8	FBPL2.7/4-1/8	11	8	22	0.011
				4x6	NPT1/8	FBPL4/6-1/8	11	11	25	0.016
				4x6	NPT1/4	FBPL4/6-1/4aV	11	11	29	0.026
				6x8	NPT1/8	FBPL6/8-1/8	14	13	25	0.016
				6x8	NPT1/4	FBPL6/8-1/4	12	13	29	0.023
				8x10	NPT1/4	FBPL8/10-1/4	14	16	30	0.031
				8x10	NPT3/8	FBPL8/10-3/8	14	16	31	0.040
				10x12	NPT3/8	FBPL10/12-3/8	14	17	33	0.040


F3BPL

Stud Fitting, Male BSPT Thread

	Nickel-plated brass			ØD			F	F1	H	kg
				2.7x4	R1/8	F3BPL2.7/4-1/8	10	8	20.5	0.009
				4x6	R1/8	F3BPL4/6-1/8	10	11	23.5	0.016
				4x6	R1/4	F3BPL4/6-1/4	14	11	26.5	0.025
				6x8	R1/8	F3BPL6/8-1/8	12	13	23.5	0.015
				6x8	R1/4	F3BPL6/8-1/4	14	13	26.5	0.023
				6x8	R3/8	F3BPL6/8-3/8	17	13	27.6	0.026
				7.5x10	R1/4	F3BPL7.5/10-1/4	14	16	27.5	0.031
				7.5x10	R3/8	F3BPL7.5/10-3/8	17	16	28.6	0.037
				8x10	R1/4	F3BPL8/10-1/4	14	16	27.5	0.031
				8x10	R3/8	F3BPL8/10-3/8	17	16	28.6	0.043
				10x12	R3/8	F3BPL10/12-3/8	17	17	30.1	0.036
				11x14	R3/8	F3BPL11/14-3/8	19	22	32.5	0.058

F4BPL


Stud Fitting, Male BSPP Thread

	Nickel-plated brass			ØD	C		E	F	F1	H	kg
				4x6	G1/8	F4BPL4/6-1/8	8	14	11	26	0.021
				6x8	G1/4	F4BPL6/8-1/4	9	17	13	28	0.030

These fittings are supplied with a copper seal.

F8BPL


Stud Fitting, Male Metric Straight Thread

	Nickel-plated brass			ØD	C		E	F	F1	H	kg
				6x8	M10x1	F8BPL6/8M10	7	14	13	28	0.021
				6x8	M12x1.25	F8BPL6/8M12	7	17	13	28	0.024

These fittings are supplied with a copper seal.

Fitting Dimensions

D: Tube O.D. (mm)	C: Metric Thread	D1: Bore Diameter (mm)	F: Hex (mm)	H: Tube Insertion Length (mm)
4x2.7	M6x0.75	1.5	8	4.5
6x4	M9x0.75	3	11	6.5
8x6	M11x0.75	5	13	6.5
10x7.5	M13x1	6.5	17	7
10x8	M13x1	6.5	17	7
12x10	M15x1.25	9	17	7.5
14x11	M18x1.50	9.5	22	8.5



Stud Fittings

CBPL Stud Elbow, Male NPT Thread

	Nickel-plated brass									
	ØD	C		F	H	J	L	kg		
	2.7x4	NPT1/8		8	18	8	22	0.019		
	4x6	NPT1/8		11	18	8	24	0.023		
	4x6	NPT1/4		11	23	10	25	0.036		
	6x8	NPT1/8		13	19	10	25	0.027		
	6x8	NPT1/4		13	23	10	25	0.034		
	8x10	NPT1/4		16	24	12	28	0.058		
	8x10	NPT3/8		16	25	12	28	0.059		
	10x12	NPT3/8		17	27	14	32	0.051		

C3BPL Stud Elbow, Male BSPT Thread

	Nickel-plated brass									
	ØD	C		F	H	J	L	kg		
	2.7x4	R1/8		8	17	8	22	0.018		
	4x6	R1/8		11	17	8	24	0.022		
	4x6	R1/4		11	21.5	10	25	0.031		
	6x8	R1/8		13	18	10	25	0.025		
	6x8	R1/4		13	21.5	10	25	0.031		
	6x8	R3/8		13	23.1	12	27	0.050		
	7.5x10	R1/4		16	22.5	12	28	0.057		
	7.5x10	R3/8		16	23.1	12	28	0.058		
	8x10	R1/4		16	21.5	12	28	0.057		
	8x10	R3/8		16	23.1	12	28	0.058		
	10x12	R3/8		17	25.1	14	32	0.052		
	11x14	R3/8		22	25.1	16	34	0.094		

C4BPL Stud Elbow, Male BSPP Thread

	Nickel-plated brass, NBR									
	ØD	C		E	F	F1	H	J	L	kg
	6x8	G1/4		7	13	13	27	12	27	0.063

These fittings are supplied with nitrile seals.

C8BPL Stud Elbow, Male Metric Straight Thread


	Nickel-plated brass, NBR									
	ØD	C		E	F	F1	H	J	L	kg
	6x8	M10x1		7	14	13	27.25	10	21.5	0.031
	6x8	M12x1		7	13	13	26	12	25	0.063

These fittings are supplied with nitrile seals.

Stud Fittings


RBPL

Stud Run Tee, Male NPT Thread

	Nickel-plated brass		ØD	C		F	H	H1	H2	J	kg
			4x6	NPT1/8	RBPL4/6-1/8	11	42	24	18	8	0.037
			4x6	NPT1/4	RBPL4/6-1/4	11	48	25	23	10	0.050
			6x8	NPT1/4	RBLP6/8-1/4	13	48	25	23	10	0.046


R3BPL

Stud Run Tee, Male BSPT Thread

	Nickel-plated brass		ØD	C		F	H	H1	H2	J	kg
			4x6	R1/8	R3BPL4/6-1/8	11	42	24	17	8	0.035
			4x6	R1/4	R3BPL4/6-1/4	11	48	25	21.5	10	0.048
			6x8	R1/8	R3BPL6/8-1/8	13	44	25	18	10	0.037
			6x8	R1/4	R3BLP6/8-1/4	13	48	25	21.5	10	0.045


SBPL

Stud Branch Tee, Male NPT Thread

	Nickel-plated brass		ØD	C		F	H	J	L	L1	kg
			4x6	NPT1/8	SBPL4/6-1/8	11	18	8	48	24	0.035
			4x6	NPT1/4	SBPL4/6-1/4	11	23	10	50	25	0.050
			6x8	NPT1/4	SBPL6/8-1/4	13	23	10	50	25	0.049


S3BPL

Branch Tee, Male BSPT Thread

	Nickel-plated brass		ØD	C		F	H	J	L	L1	kg
			4x6	R1/8	S3BPL4/6-1/8	11	17	8	48	24	0.035
			4x6	R1/4	S3BPL4/6-1/4	11	21.5	10	50	25	0.048
			6x8	R1/8	S3BPL6/8-1/8	13	18	10	50	25	0.037
			6x8	R1/4	S3BLP6/8-1/4	13	21.5	10	50	25	0.045

COR4BPL

Single Banjo, Male BSPP Thread


	Nickel-plated brass		ØD	C		E	F	F1	H	H1	L	kg
			4x6	G1/8	COR4BPL4/6-1/8	7	14	11	27	16	24	0.068
			4x6	G1/4	COR4BPL4/6-1/4	8	19	11	29	17	26	0.096
			6x8	G1/8	COR4BPL6/8-1/8	7	14	13	27	16	25	0.068
			6x8	G1/4	COR4BLP6/8-1/4	8	19	13	30	17	27	0.096

These parts are supplied with peripheral seals.
The banjo bolt is made of steel.

PL Tube-to-Tube and Complementary Fittings


HBPL

Equal Tube-to-Tube Connector

	Nickel-plated brass 	ØD		F	F1	L	kg
		2.7x4	HBPL2.7/4	7	8	24	0.010
		4x6	HBPL4/6	10	11	30	0.021
		6x8	HBPL6/8	12	13	30	0.022
		8x10	HBPL8/10	14	16	32	0.043
		10x12	HBPL10/12	16	17	36	0.056
		11x14	HBPL11/14	19	22	40	0.087


JBPL

Equal Tee

	Nickel-plated brass 	ØD		F	J	L	L1	kg
		2.7x4	JBPL2.7/4	8	8	44	22	0.024
		4x6	JBPL4/6	11	8	48	24	0.042
		6x8	JBPL6/8	13	10	50	25	0.045
		7.5x10	JBPL7.5/10	16	12	56	28	0.086
		8x10	JBPL8/10	16	12	56	28	0.085
		10x12	JBPL10/12	17	14	64	32	0.100
		11x14	JBPL11/14	22	16	68	34	0.168


WBPL

Equal Bulkhead Connector

	Nickel-plated brass 	ØD		F	F1	F2	K_{max}	L	L1	T_{min}	kg
		4x6	WBPL4/6	13	11	13	5	39	22	M9x0.75	0.030
		6x8	WBPL6/8	14	13	16	5	39	22	M11x0.75	0.032
		8x10	WBPL8/10	16	16	17	5	43	24	M13x1	0.057
		10x12	WBPL10/12	19	17	19	5	46	26	M15x1.25	0.064
		11x14	WBPL11/14	22	22	22	5	50	28	M18x1.5	0.112

BPLM

Nut

	Nickel-plated brass 	ØD	C		F	L	kg
		2.7x4	M6x0.75	BPL4M	8	10	0.003
		4x6	M9x0.75	BPL6M	11	13	0.006
		6x8	M11x0.75	BPL8M	13	13	0.008
		7.5x10	M13x1	BPL10M	16	14	0.014
		8x10	M13x1	BPL10M	16	14	0.014
		10x12	M15x1.25	BPL12M	17	16	0.012
		11x14	M18x1.5	BPL14M	22	18	0.025



Parker Legris Compression Fittings卡套式接头

联系方式：

信德迈科技(北京)有限公司 CNMEC Technology

地址:北京朝阳区望京街10号望京SOHO-T1-C座2115室

邮编：100102

Tel: 010-84282935, 8428 3983 13910962635

Fax: 010-84288762

email: sales@cnmec.biz

web: <http://www.cnmec.biz>