



Data sheet

Quick connect coupling

Series 74

Coupling: 74KB

Plug: 74SB

DN: 11 = 95 mm²

Working pressure (static): 0 up to 150 bar

Working temperature: -20°C up to +100°C (depending on the seal material and medium)

Single shut off <input type="checkbox"/>	Single hand operation <input type="checkbox"/>	ULTRA-FLO-Valve <input type="checkbox"/>
Double shut off <input checked="" type="checkbox"/>	Two hand operation <input checked="" type="checkbox"/>	Pipe-valve <input type="checkbox"/>
Straight through <input type="checkbox"/>	Ball locking system <input checked="" type="checkbox"/>	U-Cup-Seal <input type="checkbox"/>
Self venting <input type="checkbox"/>	Pin locking system <input type="checkbox"/>	O-Ring-Seal <input checked="" type="checkbox"/>
Safety lock <input type="checkbox"/>	Coupling anti-splash <input checked="" type="checkbox"/>	
Dry Break <input type="checkbox"/>	Plug anti-splash <input checked="" type="checkbox"/>	

Materials:	Standard	Version AISI 303	AISI 316 L
Back body	Brass	AISI 303	AISI 316 L
Sleeve	Brass	AISI 303	AISI 316 L
Valve	Brass	AISI 303	AISI 316 L
Spring	AISI 301	AISI 316 L	AISI 316 L
Locking Balls	AISI 420	AISI 316	AISI 316
Seals	Buna N	Viton	Viton
Plug	Brass	AISI 303	AISI 316 L

Description:

The 74KB series is a double shut-off hydraulic coupling made of non-rusting materials used for liquid mediums. It is a two hand operated coupling. The sleeve must first be pulled back before it can be connected. The plug profile is manufactured in accordance with ISO-7241-1 series B. The 74KB series can be used for liquids, paper machines, rail vehicle, refrigerating circuit.

Interchangeability:
ISO-7241-1 series B

Versions / special equipment (in part not for all versions, others upon request):

seal material Buna N, Viton, Kalrez, Ethylen-Propylen;
surface nickel plated, chrome plated, durnicoat;
oil and grease free, silicon free;

Test values at 20°C (depending on the version):

Flow-rate air:	2430 l/min at 6 bar inlet pressure and 0,5 bar pressure drop		
Flow-rate water:	33 l/min at 0,5 bar pressure drop		
Vacuum coupling:	min. - %	Weight coupling:	app. 390 g
Vacuum plug:	min. - %	Weight plug:	app. 115 g
Vacuum connected:	min. 87 %	Leakage rate / dead volume:	app. - ml
Connecting force:	w/o pressure app. 100 N	at 6 bar inlet pressure	app. - N
Disconnecting force:	w/o pressure app. 50 N	at 6 bar inlet pressure	app. - N
Safety factor:	at least 4-times	Burst-pressure:	at least 600 bar
Fatigue:	5000 cycles connecting/disconnecting tightness and function O.K.		

Revision	Date	Name		Date	Name	Document-no.:
			Made.	14.04.04	schwab	DB-74KB-SB-engl
			Check	14.04.04	schwab	
			Stand.			