

RECTUS Series 29KA



Nominal Diameter

130 mm² = **13**



Brass/Steel

Technical Description

Extremely robust steel coupling system with UltraFlo technology. Especially suitable in building or mining. Compact design prevents extreme dirtying on the sleeve and plug profile.

Advantages

Single handed operation. Low pressure drop. High flow valve.

Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Interchangeability



RECTUS Design

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart



Material

Coupling

Back Body
Sleeve
Valve
Spring and Locking Ring
Locking Balls
Seals

Standard

Steel, Zinc Plated
Steel Hardened, Zinc Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug

Steel Hardened, Zinc Plated

65% of actual size




Low Pressure

Couplings

RECTUS Series 29KA

Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
G 1/2	32	78	40	13					Standard	29KA IW21 SPZ
G 3/4	32	78	40	16					Standard	29KA IW26 SPZ




Female Thread

⚠ Please consider our security advices on the pages 12/13 ⚠



Plugs

RECTUS Series 29KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm		76	22	49					Standard	29SF TF13 SPZ
	19 mm	34	122	40	36					Standard	29SF TF19 SPZ



Plugs

RECTUS Series 29KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	24	48		13					Standard	29SF AW21 SPZ
	G 3/4	32	48		14					Standard	29SF AW26 SPZ
 <p>Female Thread</p>	G 1/2	27	44		12					Standard	29SF IW21 SPZ
	G 3/4	32	48		16					Standard	29SF IW26 SPZ

Recoil Eliminator

RECTUS Series 29KA

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	13 mm	32	93		28					Standard	29SR TF13 SPZ
	19 mm	32	101		36					Standard	29SR TF19 SPZ
 <p>Plastic Hose Connection</p>	13 x 16 mm	32	83	11	8	24		M 22 x 1	Standard	29SR KO16 SPZ	