

Nominal Diameter

13 = 133 mm²

RECTUS Series



88

actual size



Technical Description

The 86, 87 and 88 RECTUS Moldtite coupling series were especially developed for connecting coolant lines and injection molds. Countersunk plugs can easily be connected and disconnected because of the extended sleeve. The angular connections prevent kinks from forming in the hose.

Advantages

Available in single shut-off or straight-through versions. The shut-off couplings (with valve) are equipped with nickel-plated sleeves for quick and accurate visual differentiation.

Working Temperature*


-15°C up to +200°C (FKM) depending on the medium.

*At a temperature below -20°C and above +150°C specials seals are available on request.

Working Pressure

PB = 15 bar, maximum static working pressure with safety factor of 4 to 1.

Chart



Material

- Coupling
- Back Body
- Valve Body
- Sleeve
- Sleeve
- Valve
- Locking Balls
- Seals
- Spring and Locking Ring

Standard

- Brass
- Brass
- Brass (without Valve)
- Brass, Nickel Plated (with Valve)
- Brass
- AISI 420
- FKM
- AISI 420

Plug

Brass

Couplings


RECTUS Series 88

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	DS	
<p>Hose Barb</p>	13 mm		82	32	25					with Valve	88KA TF13 MVX	■ □	
										without Valve	88KF TF13 MVX	■ □	
	19 mm		89	32	32						with Valve	88KA TF19 MVX	■ □
											without Valve	88KF TF19 MVX	■ □

DS = Delivery Status: ■ in stock □ on short call □ medium term delivery



Couplings

RECTUS Series 88

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	DS
 <p>Hose Barb 90°</p>	13 mm		77	32	28,5					with Valve	88KA TR13 MVX	<input type="checkbox"/>
										without Valve	88KF TR13 MVX	<input type="checkbox"/>
	19 mm		77	32	32					with Valve	88KA TR19 MVX	<input type="checkbox"/>
										without Valve	88KF TR19 MVX	<input type="checkbox"/>

Plugs

RECTUS Series 88

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	DS
 <p>Male Thread</p>	R 1/4	22	38		12					without Valve	88SF AK13 MXX	<input type="checkbox"/>
	R 3/8	22	38		12					without Valve	88SF AK17 MXX	<input type="checkbox"/>
	R 1/2	22	44		17					without Valve	88SF AK21 MXX	<input type="checkbox"/>
	R 3/4	29	45		16					without Valve	88SF AK26 MXX	<input type="checkbox"/>
 <p>Female Thread</p>	G 3/8	22	40		13					without Valve	88SF IW17 MXX	<input type="checkbox"/>
	G 1/2	24	45		19					without Valve	88SF IW21 MXX	<input type="checkbox"/>

DS = Delivery Status:

in stock

on short call

medium term delivery



Parker Rectus快速接头授权分销商联系方式：

信德迈科技(北京)有限公司 CNMEC Technology Company

地址：北京市朝阳区望京街10号望京SOHO-T1-C座2115室

邮编：100102

电话：010-8428 2935,8428 3983

手机：139 1096 2635

Http：//www.cnmec.biz

E-mail：sales@cnmec.biz

传真：010-8428 8762