



Couplings for High Pressure Water

TEMA Series T3800

	Conne- ction A	Hex SW	L mm	D mm	Valve	Working press. in bar	Version	Seal	Part Number	DS
 Female Thread	G 3/8	24	40	34	without	350	High Pressure Water	NBR	T3810 H	■□
	G 3/8	29	40	34	without	350	High Pressure Water	NBR	T3810 H2	■□
	G 3/8	24	40	34	without	350	High Pressure Water	FKM	T3810 HV	■□
	G 3/8	29	40	34	without	350	High Pressure Water	FKM	T3810 H2V	■□
	G 3/8	24	40	34	without	350	High Pressure Water	EPDM	T3810 HEP	■□
	G 3/8	29	40	34	without	350	High Pressure Water	EPDM	T3810 H2EP	■□


Couplings with Pressure Eliminator

TEMA Series T3800

	Conne- ction A	Hex SW	L mm	D mm	Valve	Working press. in bar	Version	Seal	Part Number	DS
 Female Thread	G 3/8	24	60	34	with	350	Standard	NBR	T3811	■□
	G 3/8	24	60	34	with	350	Standard	FKM	T3811 V	■□
	G 3/8	24	60	34	with	300	Stainless Steel	FKM	T3811 RV ²⁾	■□
	G 3/8	24	60	34	with	300	Stainless Steel	FKM	T3811 RFV ¹⁾ ²⁾	■□

Plugs


TEMA Series T3800

	Conne- ction A	Hex SW	L mm	D mm	Valve	Working press. in bar	Version	Seal	Part Number	DS
 Female Thread	G 3/8	22	42	24	with	350	Standard	NBR	T3820	■□
	G 3/8	22	42	24	with	350	Standard	FKM	T3820 V	■□
	G 3/8	22	42	24	with	50	Brass	NBR	T3820 M	■□
	G 3/8	22	42	24	with	50	Brass	FKM	T3820 MV	■□
	G 3/8	22	42	24	with	300	Stainless Steel	FKM	T3820 RV ²⁾	■□
	G 3/8	22	42	24	with	300	Stainless Steel	NBR	T3820 RF ¹⁾ ²⁾	■□
	G 3/8	22	42	24	with	300	Stainless Steel	FKM	T3820 RFV ¹⁾ ²⁾	■□
	G 3/8	22	38	24	without	350	Standard		T3820 UV	■□
	G 3/8	22	38	24	without	300	Stainless Steel		T3820 RUV ²⁾	■□
	G 3/8	22	38	24	without	170	Stainless Steel		T3820 RFUV ²⁾ ³⁾	■□

¹⁾ Valve made of brass²⁾ For pulsating pressure, the pressure must not exceed 50 % of the given value³⁾ Suitable for high pressure water, AISI 303


Plugs with Pressure Eliminator

TEMA Series T3800

	Conne- tion A	Hex SW	L mm	D mm	Valve	Working press. in bar	Version	Seal	Part Number	DS
	G 3/8	22	43	24	with	350	Standard	NBR	T3821	■
	G 3/8	22	43	24	with	350	Standard	NBR	T3821 V	■□
	G 3/8	22	43	24	with	300	Stainless Steel	FKM	T3821 RV ²⁾	■□
	G 3/8	22	43	24	with	300	Stainless Steel	FKM	T3821 RFV ²⁾	■□

Lubrication Nipple

TEMA Series T3800

	Description	L mm	D mm	Part Number	DS
	Coupling	36	36	TGR3	■□


Seal-Kit for Coupling

TEMA Series T3800

	Description	Material	Part Number	DS
	Coupling	NBR	T3800-PSN	■□
	Coupling	FKM	T3800-PSV	■□
	Further sealing materials on request.			

Dust Protection

TEMA Series T3800

	Description	L mm	D mm	Material	Color	Part Number	DS
	for coupling	145	54	PVC	Blue	T3816	■
	for plug	145	46	PVC	Blue	T3826	■
	for coupling	145	54	PVC	Yellow	T3816 Y	■
	for plug	145	46	PVC	Yellow	T3826 Y	■
	Further colors on request.						

¹⁾ Valve made of brass.

²⁾ For pulsating pressure, the pressure must not exceed 50 % of the given value

³⁾ Material, AISI 420 hardened